



1. Mechanical Dimensions





SUGGESTED PCB LAYOUT

Notes:

1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. All listed parameters are to be within tolerance from -40C to +85C unless otherwise noted.
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: ±0.004"(0.102mm)
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component

2. Schematic:



3. Electrical Specifications: @25°C

OCL: Pins 1-3 1.02mH Typical @10KHz 100mV

Pins 1-3 660uH Min @10KHz 100mV

Q: Pins 1-3 8 Min @10KHz 100mV

DCR: Pins 1-3 0.600 Ohms Max

Pins 6-4 0.800 Ohms Max

Voltage Time: 18.4VuS

URNS RATIO: (1-3:6-4)=1:1.33±3%

SRF: Pins 1-3 TBD KHz Min

ISOLATION: 2000Vac

DOC. REV: A/2

XFMRs Inc www.XFMRs.com		Title: MAX253 Transformer	
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xxx ±0.010 Dimensions in INCH	P/N: XF0013-2S1	REV. A	
	DWN.	Yuan	Sep-28-15
SHEET 1 OF 1	CHK.	YK Liao	Sep-28-15
	APP.	Joe Huff	Sep-28-15

PROPRIETARY

Document is the property of XFMRs Group & is not allowed to be duplicated without authorization.