


<b>Sales Region</b>	USA/China/ASEAN/India
<b>Series</b>	PHV
<b>Model</b>	
<b>Status</b>	 Production
<b>Option</b>	
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input	Single-phase
Input Voltage Range[AC]	104 to 126VAC
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	2000Vdc
Output Voltage Range[DC]	0 to 2000V
Rated Output Current	300mA
Output Current	0 to 300mA
Rated Output Power	700W
Polarity	Floating
Power Factor	0.72
Efficiency	90% Typ.
Voltage Ripple Noise	600mV

### Package Type & Size

Package / Mounting	Rack mount
Width(W)	443mm Nom. (17.44in Nom.)
Height(H)	133mm Nom. (5.24in Nom.)
Depth(D)	350mm Nom. (13.78in Nom.)
Weight	9000g Typ. (19.8lbs Typ.)

### Other

Operating Temp. Range	0 to 40°C
Storage Temp. Range	0 to 40°C
Cooling	Forced air
Safety Standard(Certified)	
Safety Standard(Conformed)	EN61010-1 CE Mark
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.