Marktech Optoelectronics

Infrared Point Source Emitter

Product No: **MTPS3085MC**

Peak Emission Wavelength: 855nm

The 850nm Point Source Series is designed for applications requiring high accuracy and precision as well as uniform spectral emission. Custom package solutions and sorting are available.



FEATURES

> 3.5×2.2×1.24 Flat Top Ceramic SMT
> Emitting Window Diameter Φ 50μm
> High Reliability / High Output Power

APPLICATIONS

> Optical Scanning
> Linear & Rotary Encoder
> Edge Sensing
> Optical Sensors

Absolute Maximum Ratings (Ta=25°C)


ITEMS	SYMBOL	RATINGS	UNIT
Forward Current (DC)	IF	100	mA
Forward Current (Pulse)*1	IFP	0.8	A
Reverse Voltage	VR	5	V
Power Dissipation	PD	190	mW
Operating Temperature Range	Topr	-20 ~ +85	°C
Storage Temperature Range	Tstg	-30 ~ +100	°C


*1: Tw=10μsec, T=10msec.


Electrical & Optical Characteristics (Ta = 25°C)


ITEMS	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Power Output	PO	IF=20mA	--	3.0	--	mW
Forward Voltage	VF	IF=20mA	--	1.7	2.2	V
Reverse Current	IR	VR=5V	--	--	100	μA
Peak Emission Wavelength	λp	IF=20mA	--	855	--	nm
Spectral Line Half Width	Δλ	IF=20mA	--	40	--	nm
Half Intensity Beam Angle	Θ	IF=20mA	--	±50	--	deg

2011-05-23











Unit: mm, Tolerance: ±0.2

2011-05-23


SPECTRAL OUTPUT




FORWARD I-V CHARACTERISTICS




RELATIVE POWER vs FORWARD CURRENT



RADIATION PATTERN



2011-05-23



The information contained herein is subject to change without notice.

2011-05-23