

## Han F+B CA 17D 0,5mm<sup>2</sup> m/- st/- PUR 10,0m



Image is for illustration purposes only. Please refer to product description.

Part number	33 50 410 0306 100
Specification	Han F+B CA 17D 0,5mm <sup>2</sup> m/- st/- PUR 10,0m
HARTING eCatalogue	<a href="https://b2b.harting.com/33504100306100">https://b2b.harting.com/33504100306100</a>

### Identification

Category	System cabling
Series	Han <sup>®</sup> F+B
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	Male Hood
Type of cable	Copper cable (round)

### Version

Cable length	10 m
Number of cores	17
Core structure	0.5 mm <sup>2</sup>
Number of contacts	17
PE contact	Yes

### Technical characteristics

Rated current	10 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3
Limiting temperature	-20 ... +80 °C moved -40 ... +80 °C unmoved
Degree of protection acc. to IEC 60529	IP69



Pushing Performance

## Technical characteristics

Minimum bending radius	10x Cable diameter (repeated bending)
	5x Cable diameter (singular bending)

## Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	Grey

## Specifications and approvals

Specifications	EN 50525-1
	IEC 60228
	EN 50363-3
	EN 50363-10-2
Approvals	Ecolab Topactive 200
	Ecolab Topactive 500
	Ecolab Topactive OKTO
	Ecolab Topax 66
	Ecolab Topax 990

## Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85444290
eCl@ss	27060311 Assembled sensor actuator-line