


# Servo motor EMME-AS-40-M-LV-ASB

Part number: 2082446

FESTO



## Data sheet

Feature	Value
Number of pole pairs	2
Type code	EMME-AS
Rotor position sensor	Absolute encoder, single-turn
Rotor position sensor interface	HIPERFACE®
Rotor position sensor measuring principle	Capacitive
Max. rotational speed	10000 1/min
Nominal rotary speed	9000 1/min
Brake DC operating voltage	24 V
Continuous stall current	1.6 A
Insulation protection class	F
Brake power consumption	8 W
Motor constants	0.175 Nm/A
Nominal operating voltage DC	360 V
Motor nominal power	200 W
DC nominal voltage	360 V
Motor nominal current	1.2 A
Typical rotor position sensor resolution	12 bit
Rotor position encoder, typical angular accuracy	20 arcmin
Rotor position encoder, sinusoidal/cosinusoidal periods per revolution	16
Phase-phase winding resistance	8.6 Ohm
Winding inductance phase-phase	4.51 mH
Type of winding switch	Star inside
Peak current	6.4 A
Voltage constant, phase-to-phase	13.2 mVmin
Rating class according to EN 60034-1	S1
CE marking (see declaration of conformity)	As per EU EMC directive As per EU low voltage directive
Corrosion resistance class (CRC)	0 - No corrosion stress
Storage temperature	-20 °C ... 70 °C
Relative air humidity	0 - 90 %
Degree of protection	IP21
Ambient temperature	-10 °C ... 40 °C
Certification	RCM compliance mark c UL us - Recognized (OL)
Total output inertia moment	0.079 kgcm <sup>2</sup>
Brake holding torque	0.4 Nm

Feature	Value
Brake mass moment of inertia	0.014 kgcm <sup>2</sup>
Nominal torque	0.21 Nm
Peak torque	1.4 Nm
Stall torque	0.35 Nm
Permissible axial shaft load	12 N
Permissible radial shaft load	115 N
MTTF, subcomponent	371 years, holding brake
MTTFd, subcomponent	340 years, rotor position sensor
Switching cycles, holding brake	5 million idle actuations (without friction work!)
Product weight	850 g
Electrical connection technology	Plug
Note on materials	Contains paint-wetting impairment substances RoHS-compliant
Conforms to standard	IEC 60034