
Rating	18A 125VAC 10A 277VAC 3/HP 21A 14V DC
Contact Resistance	50m ohm max.
Insulation Resistance	DC 500V 100M ohm min.
Dielectric Strength	AC 1500V 1 minute
Operating Temperature	-20° C ~ 85°C

Mounting Hole



Thickness	X	Y
0.75 - 1.25	21.2 + 0.1	36.6 + 0.1
1.25 - 2.00	21.2 + 0.1	36.8 + 0.1
2.00 - 3.00	21.2 + 0.1	37.0 + 0.1


Circuit Diagram



SPDT ON - OFF- ON

BASE COLOR: Black

BUTTON COLOR: Black



RoHS Compliant

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO CW INDUSTRIES INCORPORATED AND ITS AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN CW INDUSTRIES PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM CW INDUSTRIES INCORPORATED, SOUTHAMPTON, PENNSYLVANIA USA.

CW INDUSTRIES
Southampton, Pa. 18966
Tel 215.355.7080/www.cwind.com

Date Drawn: 12/21/09	Rev. 0	Unit: mm	Checked By: G. Guld	
Title: ROCKER SWITCH			CW P/N: GRB263D001NNN	