Product data sheet
Characteristics

QC816F125S
METERMAIN RINGLESS OH/UG 125A SURFACE

Price** : 1,395.00 USD



Main

Product or component type	Meter Mains
Range of product	QO
Includes	Circuit breaker 1) 2P 125 A 120/240 V AC main supply ready assembled

Complementary

Line Rated Current	125 A
Short-circuit current	22 kA
Network number of phases	1
Meter socket type	Ringless
Mounting	Surface outdoor)
Number of spaces	8
Number of circuits	16
Number of Tandem Breakers	8
Hub type	A
Electrical connection	Feed-thru lugs service ground Feed-thru lugs line side
Wire Size	AWG 8...AWG 2/0 aluminium/copper)service ground AWG 6...350 kcmil aluminium/copper)line side
Disconnect	Service disconnect (factory installed)
Main Breaker Rating	125 A
Branch Breaker Rating	100 A
Service feed location	OH UG
Bypass type	No bypass
Depth	5.41 in (137.41 mm)
Width	18.76 in (476.50 mm)
Height	41.16 in (1045.46 mm)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Product certifications	UL E-6294

Ordering and shipping details

Category	00022-QO METER MAINS
Discount Schedule	DE3A
GTIN	00785901876380
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months