


NOTE:
 1. Rating 1: DC12V 0.1A
 2. Operating force: 200gf MAX
 3. Operating Temp: -40°C ~ +85°C
 4. Mechanical Life: 200,000
 5. Ingress protection: IP67



Circuit Diagram

Mounting Holes

⑧	Rotator	—	1	POM	—	—
⑦	Spring	—	1	SUS	Plating silver	—
⑥	Contact	—	1	Cu Alloy	—	—
⑤	Sealed Circle	—	1	Silicone Rubber	—	—
④	Terminal	—	3	Cu Alloy	Plating silver	—
③	Lever	—	1	POM	Black	—
②	Case	—	1	PA	Black	—
①	Cover	—	1	PA	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE		 ELECTRONICS CO.,LTD		
DRAWN	LIUCAN	2021.04.10				
CHECKED				TITLE: MICRO SWITCHES		
APPROVALS				PART NO. K9-1268-03		
TOLERANCES ARE	30~以上	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROJ:
	10~30	±0.20				
	5~10	±0.15				
~ 5	±0.10	±2'	DRAWING NO.	—	SHEET 1 OF 1	

—	A	—	NEW	—	—	—
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.