

## ZWS15B-12/L



Sales Region	Worldwide	
Series	ZWS-B	
Status	Production	
Feature		
Option	With chassis model	
Option Lineup	Please refer to here.	
Recommended EMC Filter	Please refer to here.	
Accessories	Please refer to the catalog	



Electrical Characteristics		
Input Voltage Range[AC]	85 to 265V	
Input Voltage Range[DC]	120 to 370V	
Efficiency	83% Typ.	
Rated Output Voltage[DC]	12V	
Output Voltage Range[DC]	10.8 to 13.2V	
Maximum Output Current	1.3A	
Maximum Output Power	15.6W	

Cases Shape & Size		
Case'[] shape	PC board	
Width(W)	60mm Nom.	
Height(H)	32mm Nom.	
Depth(D)	107.5mm Nom.	
Weight	110g Typ.	

Other		
Operating Temp. Range	-10 to 70°C	
Cooling	Convection cooling	
	UL60950-1	
Safety Standard/Cortified)	CSA C22.2 No.60950-1	
Safety Standard(Certified)	EN60950-1	
	EN50178 (OV II)	
Safety Standard(Conformed)	Den-an	
Descente	This page only shows representative characteristics. Please refer to the	
Remarks	technical data for detailed specifications and conditions.	

! Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.