

NV700



<b>Sales Region</b>	Worldwide (except Japan)
<b>Series</b>	NV
<b>Model</b>	
<b>Status</b>	Production
<b>Feature</b>	Peak power capability
	for Medical instruments
	2MOPP
<b>Options</b>	Product is fully configurable
<b>Option Lineup</b>	
<b>Recommended EMC Filter</b>	
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input	Single-phase
Input Voltage Range[AC]	90 to 264Vac
Efficiency	90% Typ.
Total Maximum Output Power	1150W
Total Maximum Peak Power	1450W
Number of Outputs	Up to 8
View Configuration Options	<a href="#">Configure Now</a>

### Package Type & Size

Package / Mounting	Enclosed / Unit type
Width(W)	275.4mm Nom. (10.84in Nom.)
Height(H)	40.6mm Nom. (1.60in Nom.)
Depth(D)	125mm Nom. (4.92in Nom.)
Weight	1160g Typ. (2.6lbs Typ.)

### Other

Operating Temp. Range	0 to 50°C
Cooling	Forced air

Safety Standard(Certified)

IEC60601-1  
CSA60601-1  
EN60601-1  
ES60601-1  
UL60601-1  
IEC60950-1  
CSA60950-1  
EN60950-1  
UL60950-1  
IEC61010-1  
EN61010-1

---

Safety Standard(Conformed)

Remarks

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

---