

The high-capacity rack server

NEC Express5800/R120g-2E(Storage-Rich)



Key Features

- Support for the latest Intel® Xeon® E5-2600 v4 product family
- Up to 1 TB of high speed DDR4 memory
- 5 PCIe slots for various needs and future expansion
- Agent-less management with improved EXPRESSSCOPE Engine 3
- Wide range of operating ambient temperature from 5 to 40°C (41 to 104°F)

Overview

The Express5800/R120g-2E, a cost-effective dual-socket 2U rack server, is a right-sized server with the performance, expandability, and reliability to meet the requirements of storage-intensive workloads. Combining the new high-performance and energy efficient Intel® Xeon® E5-2600 v4

product family, large memory and storage capacity, and high performance RAID controller supporting large cache memory and 12 Gbps SAS interface, the R120g-2E is suitable for network attached storage and data backup servers.

Features

Perfect Fit for Your Storage Needs

To meet the current data growth, data centers need cost-effective storage solutions that provide superior expandability, performance, and data protection features. With up to two 12-core Intel® Xeon® E5-2600 v4 processors, 16 DIMM slots for DDR4-2400 memory, a choice of 24 2.5-inch drives or 12 3.5-inch drives, and various redundant capabilities, the R120g-2E delivers the optimal balance of performance and features to meet your storage needs.

Expandability for Data Growth

The Express5800/R120g-2E offers superior expandability to keep pace with your data growth. With two integrated gigabit NICs, four PCIe Gen3 and one PCIe Gen2 slots, up to 1 TB of memory capacity, 124 TB of storage capacity, and redundant storage options, the R120g-2E offers flexible network connectivity, superior storage expandability, and secure data protection.

Cost Savings Through Efficiency

NEC's innovative green design concepts and industry leading fan control technology allows the R120g-2E to operate at temperatures up to 40°C (104°F), therefore reducing cooling requirements. In addition, dual hot plug power supplies with cold-standby mode enable further energy savings.

Manage easy setup and deployment with NEC EXPRESSBUILDER and leverage easy management with NEC's EXPRESSSCOPE Engine 3 together with NEC ESM PRO. The extensive remote management capabilities untangle the complexities in operating and maintaining the server to alleviate the burden of administrative tasks.

Hardware Specifications

MODEL	Express5800/R120g-2E
Form factor / height	2U Rack
Number of processors	1 to 2
Processors	Intel® Xeon® Processor E5-2603 v4 (1.70 GHz/6-core/15 MB) * Intel® Xeon® Processor E5-2620 v4 (2.10 GHz/8-core/20 MB) Intel® Xeon® Processor E5-2630 v4 (2.20 GHz/10-core/25 MB) Intel® Xeon® Processor E5-2650 v4 (2.20 GHz/12-core/30 MB) ** * Supported on only 3.5-inch drive model ** Supported on only 2.5-inch drive model
Memory type	DDR4-2400 ECC RDIMM
Memory slots	16
Maximum memory	1 TB
Storage type	Hot plug 2.5-inch SAS HDD Hot plug 2.5-inch SATA HDD Hot plug 2.5-inch SAS SSD Hot plug 2.5-inch SATA SSD Hot plug 3.5-inch SATA HDD
Maximum internal drive bays	2.5-inch drive model: 16 to 26 2.5-inch with optional drive cage 3.5-inch drive model: 12 3.5-inch plus 2 2.5-inch with optional 2.5-inch drive cage
Maximum internal storage	124 TB
Removable media	-
Expansion slots	2 PCIe x16 Gen 3 2 PCIe x8 Gen 3 1 PCIe x4 Gen 2
Video (VRAM)	Integrated in the server management controller (32 MB)
Network	2 1000BASE-T plus 1 1000BASE-T for management
Redundant power supply	Optional, hot plug
Redundant cooling fan	Optional, hot plug
Power supplies	800 Watt 100-240 VAC ± 10% 50 / 60 Hz ± 3 Hz
Systems management	EXPRESSSCOPE Engine 3
Interface	1 VGA, 1 to 2 serial, 4 USB 3.0 (plus 1 internal), 2 USB 2.0 (plus 1 internal), 2 LAN, 1 management LAN
Dimensions (W x D x H) and maximum weight	448.0 x 683.8 x 87.2 mm / 17.6 x 26.9 x 3.4 in 31 kg / 68.34 lbs.
Temperature and humidity conditions (non-condensing)	Operating: 5 to 40 °C / 41 to 104 °F, 20 to 80% Non-operating: -10 to 55 °C / 14 to 131 °F, 20 to 80%
Operating systems and virtualization software	Microsoft® Windows Server® 2008 R2 Standard / Enterprise Microsoft® Windows Server® 2012 Standard / Datacenter Microsoft® Windows Server® 2012 R2 Standard / Datacenter Microsoft® Windows Server® 2016 Standard / Datacenter Red Hat® Enterprise Linux® 6 Red Hat® Enterprise Linux® 7 VMware® ESXi™ 5.5 VMware® ESXi™ 6.0 VMware® ESXi™ 6.5* * Available in March 2017

Note: For Linux support, visit the NEC website at <http://www.nec.com/en/global/prod/express/linux/>, or contact your sales representative

For further information please contact your local NEC representative or:

Corporate Headquarters (Japan)

NEC Corporation
www.nec.com

North America (USA, Canada)

NEC Corporation of America
www.necam.com

APAC (South Asia, South East Asia, Oceania)

NEC Asia Pacific Pte. Ltd.
sg.nec.com

EMEA (Europe, Middle East, Africa)

NEC Enterprise Solutions
www.nec-enterprise.com