

## Connector - C-SCF 2,5/6,3X0,8 - 3240159

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Slip-on sleeve, non-insulated, 1.5 - 2.5 mm<sup>2</sup>, 6.3 x 0.8

The figure shows a version of the article

### Product Features

- They round out the product range in terms of connectors
- The uninsulated slip-on sleeves and flat plugs are made from electrolytically tin-plated brass



### Key commercial data

Packing unit	1 1
Minimum order quantity	100 1
Weight per Piece (excluding packing)	0.86 GRM
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Dimensions

Length (b)	19.2 mm
Width (a)	6.3 mm
Material thickness (g)	0.4 mm

#### Ambient conditions

Ambient temperature (operation)	110 °C
---------------------------------	--------

#### General

Color	silver
Stripping length	8 mm
Components	Halogen-free

# Connector - C-SCF 2,5/6,3X0,8 - 3240159

## Technical data

### General

Material	Brass
----------	-------

## Classifications

### eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201
eCl@ss 8.0	27400201

### ETIM

ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC001052
ETIM 5.0	EC001052

### UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703

## Drawings

Dimensioned drawing



