Product data sheet Characteristics

8502SEG2V08

NEMA Contactor, Type S, nonreversing, Size 3, 90A, 50 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 208 VAC coil, NEMA 1

Product availability: Non-Stock - Not normally stocked in distribution facility





Main

Product Type	Contactor	
Туре	8502S	
Control Circuit Type	Common control circuit	
Control Circuit Voltage	208 V AC 60 Hz	
Contactor Type	Non-reversing	
Current Rating	90 A	<u> </u>
Number of Poles	3P	
Phase	3 phase	: <u>:</u>
Horsepower Rating	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC	sed for
Maximum Voltage Rating	600 V AC	
SCCR	Circuit-breaker 150 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC	substitute for and is not to be used for determining equability or reliability of these or
Control Units	No control units	0
Pilot Light	No indicator	retri
Auxiliary Contacts	Without	
Control Circuit Fusing	Fuse not supplied	<u> </u>
Electrical Connection	Screw clamp terminals	<u>.º</u>
Enclosure Type	NEMA 1 painted sheet steel	
Certifications	UL listed file E78351 CCN NLDX CSA	iner. This discussion
NEMA Size	3	

Height	21.81 in (554 mm)
Depth	7.99 in (203 mm)
Width	11.46 in (291 mm)

Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901787839
Nbr. of units in pkg.	1
Package weight(Lbs)	33 lb(US) (14.97 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	

Contractual warranty

Warranty	18 months	