



规格说明: Specifications:
电气特性 Electrical

- 1. 额定电流: Current Rating
1. 5A/contact terminal
- 2. 额定电压: Voltage Rating
30V DC
- 3. 接触阻抗: Contact Resistance
30 milliohms MAX
- 4. 耐电压: Dielectric Withstanding
Voltage:
500 V AC For one minuter
- 5. 绝缘阻抗: Insulation Resistance
1000MEGA ohms MIN

原材料: Raw material

- 1. 塑胶: Plastic cement:
Hing Temperature Thermoplastics
PBT/LCP Black/White
- 2. 端子: Contact: Copper Alloy C2680
- 3. 外壳: Shell: SPC/ Copper Alloy C2680
- 电镀 Electroplate
1. 端子: Contact: Plated Gold in Mating
Area:
Tin On Solder Tails
- 2. 外壳: Shell:
Nickel Plating

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED: DATE:

CHECKED: DATE:

DRAWN: DATE:

SXA 2018-07-22

TITLE:

USB-A/F-1*4P 母头 全贴 无卷边

深圳市灿科盟实业有限公司
CKMTW CHANKLEMENT INDUSTRY CO., LTD

PROD. P/N C2895042

UNIT	mm	SCALE	free	REV.	A
FILE NO.	U-USBAM04P-F001		REV.	A	HLW0