

GEN 300-50-3P208



<b>Sales Region</b>	Worldwide (except Japan)
<b>Series</b>	Genesys
<b>Model</b>	GEN3U 15kW
<b>Status</b>	Production
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



**Electrical Characteristics**

Input	3-phase
Input Voltage Range[AC]	180 to 253Vac
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	300Vdc
Output Voltage[DC]	0 to 300Vdc
Rated Output Current	50A
Output Current	0 to 50A
Rated Output Power	15kW
Efficiency	88% Typ.
Voltage Ripple Noise	0.06Vrms (5Hz to 1MHz)
Current Ripple Noise	0.02Arms (5Hz to 1MHz)

**Package Type & Size**

Package Type	3U Rack mount / Bench top
Width(W)	429mm Nom. (16.89in Nom.)
Height(H)	132.5mm Nom. (5.22in Nom.)
Depth(D)	581mm Nom. (22.87in Nom.)
Weight	43kg Typ. (94.8lbs Typ.)

**Other**

Interfaces Included	RS-232 RS-485
Interface Options	LAN (LXI compliant) USB GPIB Isolated analog current control Isolated analog voltage control
Operating Temp. Range	0 to 50°C
Safety Standard(Certified)	UL60950-1 EN60950-1
Safety Standard(Conformed)	

