

# BIBS35010

by Burndy
Catalog ID: BIBS35010

Prop 65 Notice

MULTI-PORT Single-Sided Entry.

## Product Details

### General

| | |
|---|---|
| Hex Key | 5/16 |
| Insulation | Y |
| Insulation Type | Plastisol |
| Material | Aluminum |
| Number Of Ports | 10 |
| Physical Attribute - Number of Screws | 10 |
| Physical Attribute - Screw Type | Allen |
| Plated | N |
| Plating Type | Unplated |
| Temperature Rating | 194 |
| Trade Name | UNITAP™ |
| UPC | 781810232996 |
| UPC 12 Digit | 7818102329966 |

### Dimensions

| | |
|---|---|
| Dimension - Height inch | 2.50 in |
| Dimension - L Length Overall mm | 241 mm |
| Dimension - Length Overall inch | 9.50 in |
| Dimension - Width inch | 2.32 in |
| Dimension - Width mm | 59 mm |

### Electrical Ratings

| | |
|---|---|
| Rating - Minimum Voltage | 600 |

### Conductor Related

| | |
|---|---|
| Conductor - AL Str Size Range | 10 - 350 Str |
| Conductor - Copper Str Size Range | 10 - 350 Str |
| Conductor Type | • AL C Str-Size<br>• CU C Str-Size |

### Certifications and Compliance

| | |
|---|---|
| Certification - CSA Approved | Yes |

| | |
|---|---|
| Certification - ETL | No |
| Certification - UL Listed Direct Burial | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Industry Standard(s) | UL 486A-486B |
| Standards - Industry Standards Met | UL 486A-486B |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

## Logistics

| | |
|---|---|
| Minimum Pack Quantity | 5 |

**For further technical assistance, please contact us**

**BURNDY Headquarters**
47 East Industrial Park Drive
Manchester, New Hampshire 03109

**Customer Service Hours:**
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)