FS32 thru FS345

Surface Mount Schottky Rectifier

Reverse Voltage 20~45V Forward Current 3A

Features

- Super Low VF Schottky barrier diodes
- Very low profile - typical height of 1.0 mm
- Low forward voltage drop
- Low leakage current
- Moisture sensitivity: level 1, per J-STD-020
- AEC-Q101 qualified
- High temperature soldering guaranteed: 260℃/10 seconds
- Halogen-free according to IEC 61249-2-21 definition

RoHS COMPLIANT



eSGA
(SOD-123FL)

Typical Applications

For use of fast swiching in RF module, lighting, cellular phone, portable device, power supplies and other consumer applications.

Maximum Ratings (TA = 25 °C unless otherwise noted)

Parameter	Symbol	FS32	FS33	FS34	FS345	Unit
Maximum repetitive peak reverse voltage	VRRM	20	30	40	45	V
Maximum RMS voltage	VRMS	14	21	28	31.5	V
Maximum DC blocking voltage	VDC	20	30	40	45	V
Maximum average forward rectified current	$I_{F(AV)}$[1)]	3.0				A
	$I_{F(AV)}$[2)]	2.0				
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	IFSM	60				A
Operating junction temperature range	T_J	- 55 to + 150				°C
Storage temperature range	T_{STG}	- 55 to + 150				°C

Electrical Characteristics (TA = 25 °C unless otherwise noted)

Parameter	Test Conditions	Symbol	FS32	FS33	FS34	FS345	Unit
Maximum instantaneous forward voltage	IF=3A,TA=25℃	V_F	0.51				Volts
Maximum DC reverse current at rated DC blocking voltage	TA=25℃	I_R	30				uA
	TA=125℃		10				mA
Typical junction capacitance	4.0 V, 1 MHz	C_J	195				pF
Typical thermal resistance	juntion to mount[1)]	$R_{\theta JM}$	30				℃/W
	juntion to ambient[2)]	$R_{\theta JA}$	100				

Note:1),The thermal resistance from junction to mount,mounted on aluminum P.C.B with recommended copper pads

2),The thermal resistance from junction to ambient,mounted on P.C.B with 5×5mm copper pads,2 OZ,FR4 PCB

Ratings and Characteristics Curves

(TA = 25℃ unless otherwise noted)




Figure 1.Forward Current Derating Curve




Figure 2.Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Instantaneous Forward Characteristics




Figure 4. Typical Reverse Characteristics






Figure 5. Typical Junction Capacitance

Package Outline Dimensions



DIM	Unit: mm		Unit: inch	
	MIN	MAX	MIN	MAX
A	0.9	1.08	0.035	0.043
A1	0	0.1	0.000	0.004
B	0.85	1.05	0.033	0.041
C	0.1	0.25	0.004	0.010
D	1.7	2	0.067	0.079
E	2.9	3.1	0.114	0.122
L	0.43	0.83	0.017	0.033
HE	3.5	3.9	0.138	0.154

Soldering footprint




Packing Information

Packing quantities:

3000 pcs/Reel, 40 Reels/Box; 8mm Tape, 7" Reel

Tape & Reel Specification



Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-Ark Electronics Co., Ltd.or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page.
(http://www.goodark.com)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, Please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.