
TRIAD MAGNETICS

POWER TRANSFORMER
Chassis Mount: Control Transformer

F-398U



Electrical Specifications (@25C)
1. Maximum Power: 72.0 VA
2. Primary:
   - Series: 230V 50/60 Hz
   - Parallel: 115V 50/60 Hz
3. Secondary:
   - Series: 24.0VCT @ 3.0 Amps
   - Parallel: 12.0VCT @ 6.0 Amps
4. Voltage Regulation: 10 % TYP @ full load to no load
5. Temperature Rise: 35C TYP (45C MAX allowed)

Description:
The F-398U transformer is part of a series of Triad Control transformers that have secondary voltages that are commonly utilized in various electronic, electro-magnetic and electrical control systems. These include such applications as use with relays, solenoids, small motors, speed changers, pumps, heating elements, control valves for fluid and gases, fans, blowers, electronic tubes, automatic assembly equipment, recording devices, elevators, door openers, low voltage lamps, etc.


Construction:
Wound on a single channel nylon bobbin. Materials are UL recognized, Class B (130º C) rated.


Safety:
These products are 100% hipot tested with an insulation of 1500V between primary and secondary windings as well as between the primary / secondary windings and the core.


Dimensions:
Units: In inches

A	B	C	D	E
3.406	3.812	2.812	2.250	2.250


Mounting Holes: 0.203 x 0.375”
Weight: 4.250 lbs







Schematic:



Primary:
- Series: 1 to 4, Jumper 3 to 2
- Parallel: 1 to 3, Jumper 1 to 2 and 3 to 4

Secondary:
- Series: 5 to 8, Jumper 7 to 6
- Parallel: 5 to 7, Jumper 5 to 6 and 7 to 8

RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.

* Upon printing, this document is considered “uncontrolled”. Please contact Triad Magnetics’ website for the most current version.

Web: www.TriadMagnetics.com
Phone 951-277-0757
Fax 951-277-2757

460 Harley Knox Blvd.
Perris, California 92571

Publish Date: December 4, 2013