

Apacer

The Most **Reliable**  
Storage For Industries



**SDM5A 7P/90D LP(H)**



## SDM5A 7P/90D LP(H)

### Overview

Apacer's SDM5A-M (SATA Disk Module 5A - M) is our next generation disk-on-module (DOM) series that offers elevated speed boost and higher error correction capabilities. Built with SATA 6 Gb/s interface, SDM5A-M delivers exceptional performance in data transfer. With its SATA interface compliance and compact size, this high-speed disk module defines an ideal balance of performance, capacities, reliability and cost. SDM5A-M comes in moderate capacities that are suitable to boot industrial applications and light operating systems for specific operations, while with some extra memory space for data storage. The architectural nature of SATA disk module provides higher resistance to external environmental influences and better flexibility for motherboard space. Regarding data reliability, SDM5A-M is built in with powerful ECC engine that can correct up to 40-bit per 1KB data. In addition, the controller unit of this DOM device supports wear-leveling, SMART and power failure management for data integrity. With its trustable reliability, performance and cost effectiveness, Apacer's SDM5A-M is definitely the ideal storage or cache solution for embedded and industrial computers, servers and thin clients.



(Optional)



### Feature

- 7-pin SATA connector
- Unique Hook Design
- Power Cable-less Solution
- Perfect Solution for 1U System
- TRIM Command Support
- Product Housing Selection (Optional)
- Built-in ATA Secure Erase and S.M.A.R.T. Functions
- Global Wear-Leveling and Block Management


## Specifications

<b>Model</b>	<b>SDM5A 7P/9D LP(H)</b>
<b>Interface</b>	SATA 3.0 (6Gb/s)
<b>Connector</b>	7-pin
<b>Form Factor</b>	SATA Disk Module
<b>NAND Flash Type</b>	SLC
<b>Capacity</b>	Standard Type: 1GB~16GB High-speed Type: 8GB~32GB (in cable-less type only)
<b>External DRAM</b>	No
<b>Sustained Read Performance (MB/sec)</b>	Standard Type: Up to 34 High-speed Type: Up to 435
<b>Sustained Write Performance (MB/sec)</b>	Standard Type: Up to 55 High-speed Type: Up to 215
<b>ECC Engine*</b>	Built-in 40-bit per 1K bytes BCH ECC
<b>Standard Operating Temperature ( °C )</b>	0 ~ + 70
<b>Extended Operating Temperature ( °C )</b>	-40 ~ + 85
<b>Storage Temperature ( °C )</b>	-40 ~ +100
<b>Housing</b>	Optional
<b>H/W Write Protect</b>	No
<b>Screw Hole</b>	No
<b>Cable-less Solution</b>	Optional (7+2 pin)
<b>Shock</b>	Operation: 50G, 11ms Non-operation: 1500G, 0.5ms
<b>Vibration</b>	Operation: 7.69 Grms, 20~2000 Hz/random (compliant with MIL-STD-810G) Non-operation: 4.02 Grms, 15 ~ 2000 Hz/sine (compliant with MIL-STD-810G)
<b>Operating Voltage</b>	5.0 V±5%
<b>Power Consumption</b>	Standard Type: Active mode: 165 mA & Idle mode: 65 mA High-speed Type: Active mode: 260 mA & Idle mode: 60 mA
<b>Dimension (L x W x H )</b>	Without housing: Standard type: 30.0 x 27.8 x 8.2 mm High-speed type: 30.0 x 27.8 x 7.4 mm With housing: 32.5 x 29.4 x 8.53 mm
<b>MTBF (hours)</b>	>2,000,000

## Mechanical Specification(Housing is optional)





For external power cable connection: this feature is available as an option for Standard Type.



Unit: mm

### (Optional)



For more information, contact your Apacer representative

### Global Presence

Taiwan (Headquarters)  
Apacer Technology Inc.  
Tel: +886-2-2267-8000  
Fax: +886-2-2267-2261

Europe  
Apacer Technology B.V.  
Tel: +31-40-267-0000  
Fax: +31-40-290-0686

U.S.A.  
Apacer Memory America, Inc.  
Tel: +1-408-518-8699  
Fax: 1-510-249-9551

China  
Apacer Electronic(Shanghai)  
Co., Ltd.  
Tel: +86-21-6228-9939

Japan  
Apacer Technology Corp.  
Tel: +81-3-5419-2668  
Fax: +81-3-5419-0018

India  
Apacer Technologies Pvt. Ltd.  
Tel: +91-80-41529061~3  
Fax: +91-80-41700215