
Bulletin PD-2.214 rev. E 05/02

International
IOR Rectifier

403CNQ...(R) SERIES

SCHOTTKY RECTIFIER 400 Amp



TO-244AB


Major Ratings and Characteristics


Characteristics		403CNQ...	Units
$I_{F(AV)}$	Rectangular waveform	400	A
V_{RRM}	range	80 to 100	V
I_{FSM}	@tp = 5 µs sine	25,500	A
V_F	@200Apk, T_J=125°C (per leg)	0.69	V
T_J	range	-55 to 175	°C


Description/Features

The 403CNQ center tap Schottky rectifier module series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 175 °C junction temperature. Typical applications are in high current switching power supplies, plating power supplies, UPS systems, converters, free-wheeling diodes, welding, and reverse battery protection.

- 175 °C T_J operation
- Center tap module
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability







NOTES:
1. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
2. CONTROLLING DIMENSION: MILLIMETER

Modified JEDEC
Outline TO-244AB
Dimensions in millimeters and (inches)

Voltage Ratings

	Part number	403CNQ080	403CNQ090	403CNQ100
V_R	Max. DC Reverse Voltage (V)	80	90	100
V_{RWM}	Max. Working Peak Reverse Voltage (V)			

Absolute Maximum Ratings

	Parameters	403CNQ	Units	Conditions	
$I_{F(AV)}$	Max. Average Forward Current * See Fig. 5	400	A	50% duty cycle @ T_C = 105 °C, rectangular wave form	
I_{FSM}	Max. Peak One Cycle Non-Repetitive Surge Current (Per Leg) * See Fig. 7	25,500	A	5µs Sine or 3µs Rect. pulse	Following any rated load condition and with rated V_{RRM} applied
		3300		10ms Sine or 6ms Rect. pulse	
E_{AS}	Non-Repetitive Avalanche Energy (Per Leg)	15	mJ	T_J = 25 °C, I_{AS} = 1 Amps, L = 30 mH	
I_{AR}	Repetitive Avalanche Current (Per Leg)	1	A	Current decaying linearly to zero in 1 µsec Frequency limited by T_J max. $V_A = 1.5 \times V_R$ typical	

Electrical Specifications

	Parameters	403CNQ	Units	Conditions	
V_{FM}	Max. Forward Voltage Drop (Per Leg) * See Fig. 1 (1)	0.83	V	@ 200A	T_J = 25 °C
		0.97	V	@ 400A	
		0.69	V	@ 200A	T_J = 125 °C
		0.82	V	@ 400A	
I_{RM}	Max. Reverse Leakage Current (Per Leg) * See Fig. 2 (1)	6	mA	T_J = 25 °C	V_R = rated V_R
		80	mA	T_J = 125 °C	
C_T	Max. Junction Capacitance (Per Leg)	5500	pF	$V_R = 5V_{DC}$ (test signal range 100Khz to 1Mhz) 25°C	
L_S	Typical Series Inductance (Per Leg)	5.0	nH	From top of terminal hole to mounting plane	
dv/dt	Max. Voltage Rate of Change (Rated V_R)	10000	V/ µs		

(1) Pulse Width < 300µs, Duty Cycle <2%

Thermal-Mechanical Specifications

	Parameters		403CNQ	Units	Conditions
T_J	Max. Junction Temperature Range		-55 to 175	°C	
T_{stg}	Max. Storage Temperature Range		-55 to 175	°C	
R_{thJC}	Max. Thermal Resistance Junction to Case (Per Leg)		0.20	°C/W	DC operation * See Fig. 4
R_{thJC}	Max. Thermal Resistance Junction to Case (Per Package)		0.10	°C/W	DC operation
R_{thCS}	Typical Thermal Resistance, Case to Heatsink		0.10	°C/W	Mounting surface, smooth and greased
wt	Approximate Weight		79 (2.80)	g (oz.)	
T	Mounting Torque Base	Min.	24 (20)	Kg-cm (lbf-in)	
		Max.	35 (30)		
	Mounting Torque Center Hole	Typ.	13.5 (12)		
	Terminal Torque	Min.	35 (30)		
		Max.	46 (40)		
	Case Style		TO-244AB		Modified JEDEC




Fig. 1 - Max. Forward Voltage Drop Characteristics (Per Leg)




Fig. 2 - Typical Values Of Reverse Current Vs. Reverse Voltage (Per Leg)




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage (Per Leg)




Fig. 4 - Max. Thermal Impedance Z_{thJC} Characteristics (Per Leg)




Fig. 5 - Max. Allowable Case Temperature Vs. Average Forward Current (Per Leg)




Fig. 6 - Forward Power Loss Characteristics (Per Leg)




Fig. 7 - Max. Non-Repetitive Surge Current (Per Leg)




Fig. 8 - Unclamped Inductive Test Circuit

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 05/02