Pb Free Plating Product

FML21UR/FML22UR/FML23UR/FML24UR/FML25UR/FML26UR

10 Amperes Insulated Dual Series Connection Ultra Fast Recovery Half Bridge Rectifiers

Features

- Fast switching for high efficiency
- Low forward voltage drop
- High current capability
- Low reverse leakage current
- High surge current capability


Application

- Automotive Inverters and Solar Inverters
- Plating Power Supply,SMPS and UPS
- Car Audio Amplifiers and Sound Device Systems

Mechanical Data

- Case: ITO-220AB full plastic isolated package
- Epoxy: UL 94V-0 rate flame retardant
- Terminals: Solderable per MIL-STD-202 method 208
- Polarity: As marked on diode body
- Mounting position: Any
- Weight: 1.75 gram approximately

ITO-220AB/TO-220F-3L Unit : inch (mm)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25℃ ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

	SYMBOL	FML21UR FML22UR	FML23UR FML24UR	FML25UR FML26UR	UNIT
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	200	400	600	V
Maximum RMS Voltage	V_{RMS}	140	280	420	V
Maximum DC Blocking Voltage	V_{DC}	200	400	600	V
Maximum Average Forward Rectified Current T_C=100℃(Total Device 2*5A=10A)	$I_{F(AV)}$	10.0			A
Peak Forward Surge Current, 8.3ms single Half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	100			A
Maximum Instantaneous Forward Voltage @ 5.0 A (Both Diode/Per Diode/Per Leg)	V_F	0.98	1.3	1.7	V
Maximum DC Reverse Current @T_J=25℃ At Rated DC Blocking Voltage @T_J=125℃	I_R	5.0 100			μA μA
Maximum Reverse Recovery Time (Note 1)	Trr	35			nS
Typical junction Capacitance (Note 2)	C_J	65			pF
Typical Thermal Resistance (Note 3)	$R_{\theta JC}$	3.0			℃/W
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 to +150			℃

NOTES : (1) Reverse recovery test conditions I_F = 0.5A, I_R = 1.0A, Irr = 0.25A.
(2) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts DC.
(3) Thermal Resistance junction to case.

© 1995 Thinki Semiconductor Co., Ltd.

Download from alldatasheet.com

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS





FIG.5 - TYPICAL JUNCTION CAPACITANCE



© 1995 Thinki Semiconductor Co., Ltd.

http://www.thinkisemi.com.tw/

Download from alldatasheet.com