



| 编 号 | 尺寸 (mm) | |
|---------------|---------|-------|
| | A | B |
| HC-SPH-2*2AW | 2.00 | 6.00 |
| HC-SPH-2*3AW | 4.00 | 8.00 |
| HC-SPH-2*4AW | 6.00 | 10.00 |
| HC-SPH-2*5AW | 8.00 | 12.00 |
| HC-SPH-2*6AW | 10.00 | 14.00 |
| HC-SPH-2*7AW | 12.00 | 16.00 |
| HC-SPH-2*8AW | 14.00 | 18.00 |
| HC-SPH-2*9AW | 16.00 | 20.00 |
| HC-SPH-2*10AW | 18.00 | 22.00 |
| HC-SPH-2*11AW | 20.00 | 24.00 |
| HC-SPH-2*12AW | 22.00 | 26.00 |
| | 38.00 | 42.00 |

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material:Wafer Nylon66,UL94V-0
PIN Brass Tin-plated

PCB LAYOUT

| 制图 DRAWN | 变更内容 DESCRIPTION | 日期 DATE | GENERAL TOLERANCE | | 制图 DRAWING | 钱岳生 2021、05、03 | 料号 PART NO. | HC-SPH-2*NAW | 版本 REV. | A |
|-------------|---------------------|------------|-------------------|------------|----------------|-------------------|-------------------|-------------------------|-------------|-----|
| | | | X.±0.25 | X.'±2' | 审核 CHECK | 张名 2021、05、04 | 品名 TITLE | SPH弯针 WAFER DIP TYPE | 页次 SHEET | 1/1 |
| | | | .X±0.20 | .X'±1' | 核准 APPROVAL | 张名 2021、05、05 | 客户料号 CUTL. NO. | | | |
| | | | .XX±0.15 | .XX'±0.5' | 单位 UNITS | MM | 比例 SCALE | 1:1 | | |
| | | | .XXX±0.10 | .XXX'±0.5' | 深圳市华灿天禄电子有限公司 | | | | | |