

Operating Pressure:400gf ±100gf

Operating Stroke:0.6mm±0.3

Protection Grade:IP67,IK08

Function:(ON)-OFF

Shell:SUS

Button:SUS

Rating: 50mA 48V DC

Contact Resistance: 50mΩ MAX.

Insulation Resistance: 100MΩ MIN .

Dielectric Strength: 1500VAC 1 minute

Electrical life: 50,000 cycles



Mechanical life :200,000 cycles

Operating Temperature: -20°C~80°C

Relative Air Humidity:45%~85%

Safety Approval: **RoHS**

### CUT-OUT



**D-SWITCH**  
东莞市德燃电子有限公司  
D-SWITCH ELECTRONICS CO.,LTD

公差 TOLERANCES

.X±0.5 .XX±0.3

角度 ANGLE ±1°

单位 DIMENSION UNIT mm.

版本 VERSION

A0

比例尺 SCALE

1:1

日期 DATE

2021.04.27

品名 TITLE

PBM-16Q11-FT-N-NN-S7S-A3

图号 DRAWING NO

PBM-16Q11-FT-N-NN-S7S-A3\_A0

版本 VER 变更说明 CHANGE DESCRIPTION

日期 DATE ECN NO.

核准 APPROVED BY

核对 CHECKED BY

绘图 DRAWN BY

孙成

PBM-16Q11-FT-N-NN-S7S-A3

PBM-16Q11-FT-N-NN-S7S-A3\_A0