CY7C1379C

9-Mbit (256K x 32) Flow-through SRAM with NoBL™ Architecture

Features

- **Can support up to 133-MHz bus operations with zero wait states**
  - **Data is transferred on every clock**
- **Pin compatible and functionally equivalent to ZBT™ devices**
- **Internally self-timed output buffer control to eliminate the need to use $\overline{OE}$**
- **Registered inputs for flow-through operation**
- **Byte Write capability**
- **256K x 32 common I/O architecture**
- **Single 3.3V power supply (V_{DD})**
- **Fast clock-to-output times**
  - **6.5 ns (for 133-MHz device)**
- **Clock Enable ($\overline{CEN}$) pin to suspend operation**
- **Synchronous self-timed writes**
- **Asynchronous Output Enable**
- **Available in JEDEC-standard lead-free 100-Pin TQFP, lead-free and non lead-free 165-Ball FBGA package**
- **Burst Capability—linear or interleaved burst order**
- **Low standby power**

Functional Description[1]

The CY7C1379C is a 3.3V, 256K x 32 Synchronous Flow-through Burst SRAM designed specifically to support unlimited true back-to-back Read/Write operations without the insertion of wait states. The CY7C1379C is equipped with the advanced No Bus Latency™ (NoBL™) logic required to enable consecutive Read/Write operations with data being transferred on every clock cycle. This feature dramatically improves the throughput of data through the SRAM, especially in systems that require frequent Write-Read transitions.

All synchronous inputs pass through input registers controlled by the rising edge of the clock. The clock input is qualified by the Clock Enable ($\overline{CEN}$) signal, which when deasserted suspends operation and extends the previous clock cycle. Maximum access delay from the clock rise is 6.5 ns (133-MHz device).

Write operations are controlled by the two Byte Write Select ($BW_{[A:D]}$) and a Write Enable ($\overline{WE}$) input. All writes are conducted with on-chip synchronous self-timed write circuitry.

Three synchronous Chip Enables ($\overline{CE_1}$, CE_2, $\overline{CE_3}$) and an asynchronous Output Enable ($\overline{OE}$) provide for easy bank selection and output tri-state control. In order to avoid bus contention, the output drivers are synchronously tri-stated during the data portion of a write sequence.

Logic Block Diagram–CY7C1379C (256K x 36)



Note:
1. For best-practices recommendations, please refer to the Cypress application note *System Design Guidelines* on www.cypress.com.

Selection Guide

	133 MHz	100 MHz	Unit
Maximum Access Time	6.5	7.5	ns
Maximum Operating Current	250	180	mA
Maximum CMOS Standby Current	40	40	mA

Pin Configurations

100-Pin TQFP Pinout



Pin Configurations (continued)

165-Ball FBGA Pinout
CY7C1379C (256K x 32)

	1	2	3	4	5	6	7	8	9	10	11
A	NC/576M	A	$\overline{CE}_1$	$\overline{BW}_C$	$\overline{BW}_B$	$\overline{CE}_3$	$\overline{CEN}$	ADV/$\overline{LD}$	A	A	NC
B	NC/1G	A	CE2	$\overline{BW}_D$	$\overline{BW}_A$	CLK	$\overline{WE}$	$\overline{OE}$	NC/18M	A	NC
C	NC	NC	V_{DDQ}	V_{SS}	V_{SS}	V_{SS}	V_{SS}	V_{SS}	V_{DDQ}	NC	NC
D	DQ_C	DQ_C	V_{DDQ}	V_{DD}	V_{SS}	V_{SS}	V_{SS}	V_{DD}	V_{DDQ}	DQ_B	DQ_B
E	DQ_C	DQ_C	V_{DDQ}	V_{DD}	V_{SS}	V_{SS}	V_{SS}	V_{DD}	V_{DDQ}	DQ_B	DQ_B
F	DQ_C	DQ_C	V_{DDQ}	V_{DD}	V_{SS}	V_{SS}	V_{SS}	V_{DD}	V_{DDQ}	DQ_B	DQ_B
G	DQ_C	DQ_C	V_{DDQ}	V_{DD}	V_{SS}	V_{SS}	V_{SS}	V_{DD}	V_{DDQ}	DQ_B	DQ_B
H	NC	V_{DD}	NC	V_{DD}	V_{SS}	V_{SS}	V_{SS}	V_{DD}	NC	NC	ZZ
J	DQ_D	DQ_D	V_{DDQ}	V_{DD}	V_{SS}	V_{SS}	V_{SS}	V_{DD}	V_{DDQ}	DQ_A	DQ_A
K	DQ_D	DQ_D	V_{DDQ}	V_{DD}	V_{SS}	V_{SS}	V_{SS}	V_{DD}	V_{DDQ}	DQ_A	DQ_A
L	DQ_D	DQ_D	V_{DDQ}	V_{DD}	V_{SS}	V_{SS}	V_{SS}	V_{DD}	V_{DDQ}	DQ_A	DQ_A
M	DQ_D	DQ_D	V_{DDQ}	V_{DD}	V_{SS}	V_{SS}	V_{SS}	V_{DD}	V_{DDQ}	DQ_A	DQ_A
N	NC	NC	V_{DDQ}	V_{SS}	NC	NC	NC	V_{SS}	V_{DDQ}	NC	NC
P	NC/144M	NC/72M	A	A	NC	A1	NC	A	A	A	NC/288M
R	MODE	NC/36M	A	A	NC	A0	NC	A	A	A	A

Pin Definitions

Name	TQFP	FBGA	I/O	Description
A_0, A_1, A	37,36,32,33,34,35,44,45,46,47,48,49,50,81,82,83,99,100	R6,P6,A2,A9,A10,B2 B10,P3,P4,P8,P9,P10,R3,R4,R8,R9,R10,R11	Input-Synchronous	**Address Inputs used to select one of the 256K address locations**. Sampled at the rising edge of the CLK. $A_{[1:0]}$ are fed to the two-bit burst counter.
$\overline{BW}_A$, $\overline{BW}_B$, BW_C, BW_D	93,94,95,96	B5,A5,A4,B4	Input-Synchronous	**Byte Write Inputs, active LOW**. Qualified with $\overline{WE}$ to conduct writes to the SRAM. Sampled on the rising edge of CLK.
$\overline{WE}$	88	B7	Input-Synchronous	**Write Enable Input, active LOW**. Sampled on the rising edge of CLK if CEN is active LOW. This signal must be asserted LOW to initiate a write sequence.
ADV/$\overline{LD}$	85	A8	Input-Synchronous	**Advance/Load Input**. Used to advance the on-chip address counter or load a new address. When HIGH (and $\overline{CEN}$ is asserted LOW) the internal burst counter is advanced. When LOW, a new address can be loaded into the device for an access. After being deselected, ADV/$\overline{LD}$ should be driven LOW in order to load a new address.
CLK	89	B6	Input-Clock	**Clock Input**. Used to capture all synchronous inputs to the device. CLK is qualified with $\overline{CEN}$. CLK is only recognized if $\overline{CEN}$ is active LOW.
$\overline{CE}_1$	98	A3	Input-Synchronous	**Chip Enable 1 Input, active LOW**. Sampled on the rising edge of CLK. Used in conjunction with CE_2, and $\overline{CE}_3$ to select/deselect the device.
CE_2	97	B3	Input-Synchronous	**Chip Enable 2 Input, active HIGH**. Sampled on the rising edge of CLK. Used in conjunction with $\overline{CE}_1$ and $\overline{CE}_3$ to select/deselect the device.
$\overline{CE}_3$	92	A6	Input-Synchronous	**Chip Enable 3 Input, active LOW**. Sampled on the rising edge of CLK. Used in conjunction with $\overline{CE}_1$ and CE_2 to select/deselect the device.

Pin Definitions (continued)

Name	TQFP	FBGA	I/O	Description
$\overline{OE}$	86	B8	Input-Asynchronous	**Output Enable, asynchronous input, active LOW**. Combined with the synchronous logic block inside the device to control the direction of the I/O pins. When LOW, the I/O pins are allowed to behave as outputs. When deasserted HIGH, I/O pins are tri-stated, and act as input data pins. $\overline{OE}$ is masked during the data portion of a write sequence, during the first clock when emerging from a deselected state, when the device has been deselected.
$\overline{CEN}$	87	A7	Input-Synchronous	**Clock Enable Input, active LOW**. When asserted LOW the Clock signal is recognized by the SRAM. When deasserted HIGH the Clock signal is masked. Since deasserting $\overline{CEN}$ does not deselect the device, $\overline{CEN}$ can be used to extend the previous cycle when required.
ZZ	64	H11	Input-Asynchronous	**ZZ "sleep" Input**. This active HIGH input places the device in a non-time critical "sleep" condition with data integrity preserved. For normal operation, this pin has to be LOW or left floating. ZZ pin has an internal pull-down.
DQ_s	52,53,56,57, 58,59,62,63, 68,69,72,73, 74,75,78,79, 2,3,6,7, 8,9,12,13, 18,19,22,23, 24,25,28,29	M11,L11, K11,J11, J10,K10, L10,M10, D10,E10, F10,G10, D11,E11, F11,G11, D1,E1,F1, G1,D2,E2, F2,G2,J1, K1,L1,M1, J2,K2,L2 M2	I/O-Synchronous	**Bidirectional Data I/O Lines**. As inputs, they feed into an on-chip data register that is triggered by the rising edge of CLK. As outputs, they deliver the data contained in the memory location specified by address during the clock rise of the Read cycle. The direction of the pins is controlled by $\overline{OE}$ and the internal control logic. When $\overline{OE}$ is asserted LOW, the pins can behave as outputs. When HIGH, DQ_s are placed in a tri-state condition. The outputs are automatically tri-stated during the data portion of a write sequence, during the first clock when emerging from a deselected state, and when the device is deselected, regardless of the state of $\overline{OE}$.
Mode	31	R1	Input Strap Pin	**Mode Input. Selects the burst order of the device.** When tied to GND selects linear burst sequence. When tied to V_{DD} or left floating selects interleaved burst sequence.
V_{DD}	15,41,65,91	D4,D8,E4, E8,F4,F8, G4,G8,H2, H4,H8,J4, J8,K4,K8, L4,L8,M4, M8	Power Supply	**Power supply inputs to the core of the device**.
V_{DDQ}	4,11,20,27,54, 61,70,77	C3,C9,D3, D9,E3,E9, F3,F9,G3, G9,J3,J9, K3,K9,L3, L9,M3,M9, N3,N9	I/O Power Supply	**Power supply for the I/O circuitry**.

Pin Definitions (continued)

Name	TQFP	FBGA	I/O	Description
V_{SS}	5,10,17,21, 26,40,55,60, 67,71,76,90,	C4,C5,C6, C7,C8,D5, D6,D7,E5, E6,E7,F5, F6,F7,G5, G6,G7,H5, H6,H7,J5, J6,J7,K5,K6,K 7,L5,L6,L7,M5 ,M6,M7, N4,N8	Ground	**Ground for the device**.
NC	1,16,30,38,39, 42,43,51,66,80,8 4,95,96	A1,A11,B1, B9,B11,C1, C2,C10,C11,H 1,H3,H9, H10,N1,N2, N5,N6,N7 N10,N11,P1,P 2,P5,P7, P11,R2,R5, R7	–	**No Connects**. Not Internally connected to the die. 18M, 36M, 72M, 144M, 288M, 576M, and 1G are address expansion pins and are not internally connected to the die.
V_{SS}/DNU	14	-	Ground/DNU	This pin can be connected to Ground or should be left floating.

Functional Overview

The CY7C1379C is a synchronous flow-through burst SRAM designed specifically to eliminate wait states during Write-Read transitions. All synchronous inputs pass through input registers controlled by the rising edge of the clock. The clock signal is qualified with the Clock Enable input signal ($\overline{CEN}$). If $\overline{CEN}$ is HIGH, the clock signal is not recognized and all internal states are maintained. All synchronous operations are qualified with $\overline{CEN}$. Maximum access delay from the clock rise (t_{CDV}) is 6.5 ns (133-MHz device).

Accesses can be initiated by asserting all three Chip Enables ($\overline{CE_1}$, CE_2, $\overline{CE_3}$) active at the rising edge of the clock. If Clock Enable ($\overline{CEN}$) is active LOW and ADV/$\overline{LD}$ is asserted LOW, the address presented to the device will be latched. The access can either be a read or write operation, depending on the status of the Write Enable ($\overline{WE}$). $BW_{[A:D]}$ can be used to conduct byte write operations.

Write operations are qualified by the Write Enable ($\overline{WE}$). All writes are simplified with on-chip synchronous self-timed write circuitry.

Three synchronous Chip Enables ($\overline{CE_1}$, CE_2, $\overline{CE_3}$) and an asynchronous Output Enable ($\overline{OE}$) simplify depth expansion. All operations (Reads, Writes, and Deselects) are pipelined. ADV/$\overline{LD}$ should be driven LOW once the device has been deselected in order to load a new address for the next operation.

Single Read Accesses

A read access is initiated when the following conditions are satisfied at clock rise: (1) $\overline{CEN}$ is asserted LOW, (2) $\overline{CE_1}$, CE_2, and $\overline{CE_3}$ are ALL asserted active, (3) the Write Enable input signal $\overline{WE}$ is deasserted HIGH, and 4) ADV/$\overline{LD}$ is asserted LOW. The address presented to the address inputs is latched into the Address Register and presented to the memory array and control logic. The control logic determines that a read access is in progress and allows the requested data to propagate to the output buffers. The data is available within 6.5 ns (133-MHz device) provided $\overline{OE}$ is active LOW. After the first clock of the read access, the output buffers are controlled by $\overline{OE}$ and the internal control logic. $\overline{OE}$ must be driven LOW in order for the device to drive out the requested data. On the subsequent clock, another operation (Read/Write/Deselect) can be initiated. When the SRAM is deselected at clock rise by one of the chip enable signals, its output will be tri-stated immediately.

Burst Read Accesses

The CY7C1379C has an on-chip burst counter that allows the user the ability to supply a single address and conduct up to four Reads without reasserting the address inputs. ADV/$\overline{LD}$ must be driven LOW in order to load a new address into the SRAM, as described in the Single Read Access section above. The sequence of the burst counter is determined by the MODE input signal. A LOW input on MODE selects a linear burst mode, a HIGH selects an interleaved burst sequence. Both burst counters use A0 and A1 in the burst sequence, and will wrap around when incremented sufficiently. A HIGH input on ADV/$\overline{LD}$ will increment the internal burst counter regardless of the state of chip enable inputs or $\overline{WE}$. $\overline{WE}$ is latched at the beginning of a burst cycle. Therefore, the type of access (Read or Write) is maintained throughout the burst sequence.

Single Write Accesses

Write access are initiated when the following conditions are satisfied at clock rise: (1) $\overline{CEN}$ is asserted LOW, (2) $\overline{CE_1}$, CE_2, and $\overline{CE_3}$ are ALL asserted active, and (3) the Write signal $\overline{WE}$ is asserted LOW. The address presented to the address bus is loaded into the Address Register. The write signals are latched into the Control Logic block. The data lines are automatically tri-stated regardless of the state of the $\overline{OE}$ input signal. This allows the external logic to present the data on DQs.

On the next clock rise the data presented to DQs (or a subset for Byte Write operations, see Truth Table for details) inputs is latched into the device and the write is complete. Additional accesses (Read/Write/Deselect) can be initiated on this cycle.

The data written during the Write operation is controlled by $\overline{BW}_{[A:D]}$ signals. The CY7C1379C provides Byte Write capability that is described in the truth table. Asserting the Write Enable input ($\overline{WE}$) with the selected Byte Write Select input will selectively write to only the desired bytes. Bytes not selected during a Byte Write operation will remain unaltered. A synchronous self-timed write mechanism has been provided to simplify the Write operations. Byte Write capability has been included in order to greatly simplify Read/Modify/Write sequences, which can be reduced to simple Byte Write operations.

Because the CY7C1379C is a common I/O device, data should not be driven into the device while the outputs are active. The Output Enable ($\overline{OE}$) can be deasserted HIGH before presenting data to the DQ inputs. Doing so will tri-state the output drivers. As a safety precaution, DQs and DQP_X.are automatically tri-stated during the data portion of a write cycle, regardless of the state of $\overline{OE}$.

Burst Write Accesses

The CY7C1379C has an on-chip burst counter that allows the user the ability to supply a single address and conduct up to four Write operations without reasserting the address inputs. ADV/LD must be driven LOW in order to load the initial address, as described in the Single Write Access section above. When ADV/LD is driven HIGH on the subsequent clock rise, the Chip Enables ($\overline{CE}_1$, CE_2, and $\overline{CE}_3$) and $\overline{WE}$ inputs are ignored and the burst counter is incremented. The correct $\overline{BW}_{[A:D]}$ inputs must be driven in each cycle of the burst write, in order to write the correct bytes of data.

Sleep Mode

The ZZ input pin is an asynchronous input. Asserting ZZ places the SRAM in a power conservation “sleep” mode. Two clock cycles are required to enter into or exit from this “sleep” mode. While in this mode, data integrity is guaranteed. Accesses pending when entering the “sleep” mode are not considered valid nor is the completion of the operation guaranteed. The device must be deselected prior to entering the “sleep” mode. $\overline{CE}_1$, CE_2, and $\overline{CE}_3$, must remain inactive for the duration of t_{ZZREC} after the ZZ input returns LOW.

Linear Burst Address Table (MODE = GND)

First Address A1, A0	Second Address A1, A0	Third Address A1, A0	Fourth Address A1, A0
00	01	10	11
01	10	11	00
10	11	00	01
11	00	01	10

Interleaved Burst Sequence

First Address	Second Address	Third Address	Fourth Address
A1, A0	A1, A0	A1, A0	A1, A0
00	01	10	11
01	00	11	10
10	11	00	01
11	10	01	00

ZZ Mode Electrical Characteristics

Parameter	Description	Test Conditions	Min.	Max.	Unit
I_{DDZZ}	Sleep mode standby current	$ZZ \geq V_{DD} - 0.2V$		50	mA
t_{ZZS}	Device operation to ZZ	$ZZ \geq V_{DD} - 0.2V$		$2t_{CYC}$	ns
t_{ZZREC}	ZZ recovery time	$ZZ \leq 0.2V$	$2t_{CYC}$		ns
t_{ZZI}	ZZ Active to Sleep current	This parameter is sampled		$2t_{CYC}$	ns
t_{RZZI}	ZZ inactive to exit Sleep current	This parameter is sampled	0		ns

Truth Table[2, 3, 4, 5, 6, 7, 8]

Operation	ADRESS Used	$\overline{CE_1}$	CE_2	$\overline{CE_3}$	ZZ	ADV/$\overline{LD}$	$\overline{WE}$	$\overline{BW_X}$	$\overline{OE}$	$\overline{CEN}$	CLK	DQ
Deselect Cycle	None	H	X	X	L	L	X	X	X	L	L->H	Tri-State
Deselect Cycle	None	X	X	H	L	L	X	X	X	L	L->H	Tri-State
Deselect Cycle	None	X	L	X	L	L	X	X	X	L	L->H	Tri-State
Continue Deselect Cycle	None	X	X	X	L	H	X	X	X	L	L->H	Tri-State
READ Cycle (Begin Burst)	External	L	H	L	L	L	H	X	L	L	L->H	Data Out (Q)
READ Cycle (Continue Burst)	Next	X	X	X	L	H	X	X	L	L	L->H	Data Out (Q)
NOP/DUMMY READ (Begin Burst)	External	L	H	L	L	L	H	X	H	L	L->H	Tri-State
DUMMY READ (Continue Burst)	Next	X	X	X	L	H	X	X	H	L	L->H	Tri-State
WRITE Cycle (Begin Burst)	External	L	H	L	L	L	L	L	X	L	L->H	Data In (D)
WRITE Cycle (Continue Burst)	Next	X	X	X	L	H	X	L	X	L	L->H	Data In (D)
NOP/WRITE ABORT (Begin Burst)	None	L	H	L	L	L	L	H	X	L	L->H	Tri-State
WRITE ABORT (Continue Burst)	Next	X	X	X	L	H	X	H	X	L	L->H	Tri-State
IGNORE CLOCK EDGE (Stall)	Current	X	X	X	L	X	X	X	X	H	L->H	–
Sleep MODE	None	X	X	X	H	X	X	X	X	X	X	Tri-State

Truth Table for Read/Write[2, 3]

Function (CY7C1379C)	$\overline{WE}$	$\overline{BW_A}$	$\overline{BW_B}$	$\overline{BW_C}$	$\overline{BW_D}$
Read	H	X	X	X	X
Write No Bytes Written	L	H	H	H	H
Write Byte A – (DQ_A)	L	L	H	H	H
Write Byte B – (DQ_B)	L	H	L	H	H
Write Byte C – (DQ_C)	L	H	H	L	H
Write Byte D – (DQ_D)	L	H	H	H	L
Write All Bytes	L	L	L	L	L

Notes:
2. X ="Don't Care." H = HIGH, L = LOW. $\overline{BWx}$ = 0 signifies at least one Byte Write Select is active, $\overline{BWx}$ = Valid signifies that the desired byte write selects are asserted, see Truth Table for details.
3. Write is defined by $\overline{BW_X}$, and $\overline{WE}$. See Truth Table for Read/Write.
4. When a Write cycle is detected, all I/Os are tri-stated, even during Byte Writes.
5. The DQ pins are controlled by the current cycle and the $\overline{OE}$ signal. $\overline{OE}$ is asynchronous and is not sampled with the clock.
6. $\overline{CEN}$ = H, inserts wait states.
7. Device will power-up deselected and the I/Os in a tri-state condition, regardless of $\overline{OE}$.
8. $\overline{OE}$ is asynchronous and is not sampled with the clock rise. It is masked internally during write cycles. During a read cycle DQs = Three-state when $\overline{OE}$ is inactive or when the device is deselected, and DQs = data when $\overline{OE}$ is active.

Maximum Ratings

(Above which the useful life may be impaired. For user guidelines, not tested.)

Storage Temperature .....–65°C to +150°C

Ambient Temperature with Power Applied.....–55°C to +125°C

Supply Voltage on V_{DD} Relative to GND.....–0.5V to +4.6V

Supply Voltage on V_{DDQ} Relative to GND .....–0.5V to +V_{DD}

DC Voltage Applied to Outputs in High-Z State ..... –0.5V to V_{DDQ} + 0.5V

DC Input Voltage .....–0.5V to V_{DD} + 0.5V

Current into Outputs (LOW)..... 20 mA

Static Discharge Voltage..... > 2001V (per MIL-STD-883, Method 3015)

Latch-up Current..... > 200 mA

Operating Range

Range	Ambient Temperature (T_A)	V_{DD}/V_{DDQ}
Com'l	0°C to +70°C	3.3V – 5%/+10%
Ind'l	–40°C to +85°C	

Electrical Characteristics Over the Operating Range [9, 10]

Parameter	Description	Test Conditions		Min.	Max.	Unit
V_{DD}	Power Supply Voltage			3.135	3.6	V
V_{DDQ}	I/O Supply Voltage	for 3.3V I/O		3.135	V_{DD}	V
V_{OH}	Output HIGH Voltage	for 3.3V I/O, I_{OH} = –4.0 mA		2.4		V
V_{OL}	Output LOW Voltage	for 3.3V I/O, I_{OL} = 8.0 mA			0.4	V
V_{IH}	Input HIGH Voltage	for 3.3V I/O		2.0	V_{DD} + 0.3V	V
V_{IL}	Input LOW Voltage[9]	for 3.3V I/O		–0.3	0.8	V
I_X	Input Leakage Current except ZZ and MODE	GND ≤ V_I ≤ V_{DDQ}		–5	5	µA
	Input Current of MODE	Input = V_{SS}		–30		µA
		Input = V_{DDQ}			5	µA
	Input Current of ZZ	Input = V_{SS}		–5		µA
		Input = V_{DDQ}			30	µA
I_{OZ}	Output Leakage Current	GND ≤ V_I ≤ V_{DDQ}, Output Disabled		–5	5	µA
I_{DD}	V_{DD} Operating Supply Current	V_{DD} = Max., I_{OUT} = 0 mA, f = f_{MAX}= $1/t_{CYC}$	7.5-ns cycle, 133 MHz		250	mA
			10-ns cycle, 100 MHz		180	mA
I_{SB1}	Automatic CE Power-down Current—TTL Inputs	V_{DD} = Max, Device Deselected, V_{IN} ≥ V_{IH} or V_{IN} ≤ V_{IL}, f = f_{MAX}, inputs switching	All speeds		110	mA
I_{SB2}	Automatic CE Power-down Current—CMOS Inputs	V_{DD} = Max, Device Deselected, V_{IN} ≥ V_{DD} – 0.3V or V_{IN} ≤ 0.3V, f = 0, inputs static	All speeds		40	mA
I_{SB3}	Automatic CE Power-down Current—CMOS Inputs	V_{DD} = Max, Device Deselected, V_{IN} ≥ V_{DDQ} – 0.3V or V_{IN} ≤ 0.3V, f = f_{MAX}, inputs switching	All speeds		100	mA
I_{SB4}	Automatic CE Power-down Current—TTL Inputs	V_{DD} = Max, Device Deselected, V_{IN} ≥ V_{IH} or V_{IN} ≤ V_{IL}, f = 0, inputs static	All speeds		40	mA

Notes:
9. Overshoot: V_{IH}(AC) < V_{DD} +1.5V (Pulse width less than $t_{CYC}/2$), undershoot: V_{IL}(AC)> –2V (Pulse width less than $t_{CYC}/2$).
10. $T_{Power\text{-}up}$: Assumes a linear ramp from 0V to V_{DD} (min.) within 200 ms. During this time V_{IH} < V_{DD} and V_{DDQ} ≤ V_{DD}.

Capacitance[11]

Parameter	Description	Test Conditions	100 TQFP Max.	165 FBGA Max.	Unit
C_{IN}	Input Capacitance	T_A = 25°C, f = 1 MHz, V_{DD} = 3.3V V_{DDQ}=3.3V	5	7	pF
C_{CLOCK}	Clock Input Capacitance		5	7	pF
$C_{I/O}$	I/O Capacitance		5	7	pF

Thermal Resistance[11]

Parameters	Description	Test Conditions	100 TQFP Package	165 FBGA Package	Unit
Θ_{JA}	Thermal Resistance (Junction to Ambient)	Test conditions follow standard test methods and procedures for measuring thermal impedance, per EIA/JESD51	29.41	16.8	°C/W
Θ_{JC}	Thermal Resistance (Junction to Case)		6.13	3.0	°C/W

AC Test Loads and Waveforms

3.3V I/O Test Load



Switching Characteristics Over the Operating Range[12, 13, 14, 15, 16, 17]

Parameter	Description	–133		–100		Unit
		Min.	Max.	Min.	Max.	
t_{POWER}	V_{DD}(Typical) to the First Access[14]	1		1		ms
Clock						
t_{CYC}	Clock Cycle Time	7.5		10.0		ns
t_{CH}	Clock HIGH	3.0		4.0		ns
t_{CL}	Clock LOW	3.0		4.0		ns
Output Times						
t_{CDV}	Data Output Valid after CLK Rise		6.5		7.5	ns
t_{DOH}	Data Output Hold after CLK Rise	2.0		2.0		ns
t_{CLZ}	Clock to Low-Z[15, 16, 17]	0		0		ns
t_{CHZ}	Clock to High-Z[15, 16, 17]		3.5		3.5	ns
t_{OEV}	$\overline{OE}$ LOW to Output Valid		3.5		3.5	ns
t_{OELZ}	$\overline{OE}$ LOW to Output Low-Z[15, 16, 17]	0		0		ns
t_{OEHZ}	$\overline{OE}$ HIGH to Output High-Z[15, 16, 17]		3.5		3.5	ns

Notes:
11. Tested initially and after any design or process changes that may affect these parameters.
12. Timing reference level is 1.5V when V_{DDQ}=3.3V.
13. Test conditions shown in (a) of AC Test Loads, unless otherwise noted.
14. This part has a voltage regulator internally; t_{POWER} is the time that the power needs to be supplied above V_{DD} (minimum) initially, before a read or write operation can be initiated.
15. t_{CHZ}, t_{CLZ},t_{OELZ}, and t_{OEHZ} are specified with AC test conditions shown in part (b) of AC Test Loads. Transition is measured ± 200 mV from steady-state voltage.
16. At any given voltage and temperature, t_{OEHZ} is less than t_{OELZ} and t_{CHZ} is less than t_{CLZ} to eliminate bus contention between SRAMs when sharing the same data bus. These specifications do not imply a bus contention condition, but reflect parameters guaranteed over worst case user conditions. Device is designed to achieve High-Z prior to Low-Z under the same system conditions.
17. This parameter is sampled and not 100% tested.

Switching Characteristics Over the Operating Range[12, 13, 14, 15, 16, 17] (continued)

Parameter	Description	–133		–100		Unit
		Min.	Max.	Min.	Max.	
Set-up Times						
t_{AS}	Address Set-up before CLK Rise	1.5		1.5		ns
t_{ALS}	ADV/$\overline{LD}$ Set-up before CLK Rise	1.5		1.5		ns
t_{WES}	$\overline{WE}$, $\overline{BW}_{[A:D]}$ Set-up before CLK Rise	1.5		1.5		ns
t_{CENS}	$\overline{CEN}$ Set-up before CLK Rise	1.5		1.5		ns
t_{DS}	Data Input Set-up before CLK Rise	1.5		1.5		ns
t_{CES}	Chip Enable Set-up before CLK Rise	1.5		1.5		ns
Hold Times						
t_{AH}	Address Hold after CLK Rise	0.5		0.5		ns
t_{ALH}	ADV/$\overline{LD}$ Hold after CLK Rise	0.5		0.5		ns
t_{WEH}	$\overline{WE}$, $\overline{BW}_X$ Hold after CLK Rise	0.5		0.5		ns
t_{CENH}	$\overline{CEN}$ Hold after CLK Rise	0.5		0.5		ns
t_{DH}	Data Input Hold after CLK Rise	0.5		0.5		ns
t_{CEH}	Chip Enable Hold after CLK Rise	0.5		0.5		ns

Switching Waveforms

Read/Write Waveforms[18, 19, 20]



Notes:

18. For this waveform ZZ is tied LOW.
19. When $\overline{CE}$ is LOW, $\overline{CE}_1$ is LOW, CE_2 is HIGH and $\overline{CE}_3$ is LOW. When $\overline{CE}$ is HIGH, $\overline{CE}_1$ is HIGH or CE_2 is LOW or $\overline{CE}_3$ is HIGH.
20. Order of the Burst sequence is determined by the status of the MODE (0 = Linear, 1 = Interleaved). Burst operations are optional.

Switching Waveforms (continued)

NOP, STALL and Deselect Cycles[18, 19, 21]



ZZ Mode Timing[22, 23]



Notes:
21. The IGNORE CLOCK EDGE or STALL cycle (Clock 3) illustrated $\overline{CEN}$ being used to create a pause. A write is not performed during this cycle.
22. Device must be deselected when entering ZZ mode. See truth table for all possible signal conditions to deselect the device.
23. I/Os are in High-Z when exiting ZZ sleep mode.

Ordering Information

Not all of the speed, package and temperature ranges are available. Please contact your local sales representative or visit www.cypress.com for actual products offered.

Speed (MHz)	Ordering Code	Package Diagram	Part and Package Type	Operating Range
133	CY7C1355C-133AXC	51-85050	100-Pin Thin Quad Flat Pack (14 x 20 x 1.4 mm) Lead-Free	Commercial
	CY7C1355C-133BZC	51-85122	165-ball Fine-Pitch Ball Grid Array (13 x 15 x 1.2 mm)	
	CY7C1355C-133BZXC		165-ball Fine-Pitch Ball Grid Array (13 x 15 x 1.2 mm) Lead-Free	
	CY7C1355C-133AXI	51-85050	100-Pin Thin Quad Flat Pack (14 x 20 x 1.4 mm) Lead-Free	Industrial
	CY7C1355C-133BZI	51-85122	165-ball Fine-Pitch Ball Grid Array (13 x 15 x 1.2 mm)	
	CY7C1355C-133BZXI		165-ball Fine-Pitch Ball Grid Array (13 x 15 x 1.2 mm) Lead-Free	
100	CY7C1355C-100AXC	51-85050	100-Pin Thin Quad Flat Pack (14 x 20 x 1.4 mm) Lead-Free	Commercial
	CY7C1355C-100BZC	51-85122	165-ball Fine-Pitch Ball Grid Array (13 x 15 x 1.2 mm)	
	CY7C1355C-100BZXC		165-ball Fine-Pitch Ball Grid Array (13 x 15 x 1.2 mm) Lead-Free	
	CY7C1355C-100AXI	51-85050	100-Pin Thin Quad Flat Pack (14 x 20 x 1.4 mm) Lead-Free	Industrial
	CY7C1355C-100BZI	51-85122	165-ball Fine-Pitch Ball Grid Array (13 x 15 x 1.2 mm)	
	CY7C1355C-100BZXI		165-ball Fine-Pitch Ball Grid Array (13 x 15 x 1.2 mm) Lead-Free	

Package Diagrams

100-Pin Thin Plastic Quad Flatpack (14 x 20 x 1.4 mm) (51-85050)



Package Diagrams (continued)

165-ball FBGA (13 x 15 x 1.2 mm) (51-85122)



NoBL and No Bus Latency are trademarks of Cypress Semiconductor Corporation. ZBT is a trademark of Integrated Device Technology, Inc. All product and company names mentioned in this document are the trademarks of their respective holders.

© Cypress Semiconductor Corporation, 2006. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, life saving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Document History Page

Document Title: CY7C1379C 9-Mbit (256K x 32) Flow-through SRAM with NoBL™ Architecture Document Number: 38-05688				
REV.	**ECN NO.**	**Issue Date**	**Orig. of Change**	**Description of Change**
**	286269	See ECN	PCI	New data sheet
*A	320834	See ECN	PCI	Address expansion pins/balls in the pinouts for all packages are modified as per JEDEC standard Added 133 MHz in the Ordering Information table Changed Θ_{JA} and Θ_{JC} for TQFP Package from 25 and 9 °C/W to 29.41 and 6.13 °C/W respectively Changed Θ_{JA} and Θ_{JC} for FBGA Package from 27 and 6 °C/W to 16.8 and 3.0 °C/W respectively Modified V_{OL}, V_{OH} test conditions Corrected IDD, tCDV, tCH, tDOH and tCL for 100MHz to 180 mA, 7.5 ns, 4 ns, 2 ns and 4 ns respectively Changed Snooze to Sleep in the ZZ Mode Electrical Characteristics and truth table Added Industrial operating range Added BZC package in the Ordering Information table Updated Ordering Information Table
*B	377095	See ECN	PCI	Changed I_{SB2} from 30 to 40 mA Modified test condition in note# 10 from $V_{DDQ} < V_{DD}$ to $V_{DDQ} \leq V_{DD}$
*C	408725	See ECN	RXU	Changed address of Cypress Semiconductor Corporation on Page# 1 from “3901 North First Street” to “198 Champion Court” Changed three-state to tri-state Converted from preliminary to final Modified “Input Load” to “Input Leakage Current except ZZ and MODE” in the Electrical Characteristics Table Replaced Package Name column with Package Diagram in the Ordering Information table
*D	501828	See ECN	VKN	Added the Maximum Rating for Supply Voltage on V_{DDQ} Relative to GND Updated the Ordering Information table.