



FCS-3305 Version: 1

! Power supply unit is to be ordered separately.

Zoom Dome IP Network Camera, H.265, 5-Megapixel, 802.3af PoE, IR LEDs, Indoor/Outdoor, 2.8X Optical Zoom, Vandalproof, two-way audio

The LevelOne FCS-3305 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP66 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-3305 offers 5-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

Key Features

- 5-Megapixel high-definition resolution
- Video compression: H.264, H.265
- Built-in infrared LEDs for night viewing up to 30m
- Vandal-proof IK10-rated housing
- Supports 2.8X optical zoom
- Dual power support: 12V DC/PoE (IEEE 802.3af)
- Weatherproof IP66-rated housing

Specifications

System Specifications

Standards & Protocols:

IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, CoS, ICMP, SNMP, QoS

Image Sensor:

1/1.8" Progressive Scan CMOS

Lens:

Zoom, f3.6 - 10mm / F1.5 - 2.8, P-iris

Port:

- 1 x 10/ 100 Mbps PoE 802.af
- 1 x DI/DO (Terminal Block)
- 1 x Line in/Out Terminal Block)
- 1 x DC 12V (Terminal Block)

**Button/Knob:**

Reset

Indicator:

Power

IR Cut Filter:

Support

IR LED:

30 Meter

Shutter Time:

1/5 ~ 1/16,000 sec (manual mode)

Angle of View:

79.5° - 38.1°

Video Compression:

H.265, H.264, MJPEG

Resolution:

30 fps at 2592 x 1944; 30 fps at 2048 x 1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 960;
30 fps at 1280 x 720; 30 fps at 800 x 600; 30 fps at 640 x 480; 30 fps at 320 x 240

Output Video Format:

RAW

Audio Compression:

Mono, PCM, G.711

Power Input:

DC 12V, PoE(802.3af)

Power Consumption:

8W

Data Rate:

128 Kbps - 20 Mbps (per stream) (per stream)

Storage Capacity:

MicroSDHC/SDXC memory card slot

Optical Zoom:

2.8X Optical Zoom

Features

General:

Extreme WDR (100 dB); White balance: automatic, manual, hold; Brightness; Digital image stabilizer
Contrast; Sharpness (auto); Auto gain control; 2D + 3D digital noise reduction; Defogging

PoE:

IEEE 802.3af (PoE Class3)

Security:

IP address filtering; HTTPs encryption; Password protected user levels; Anonymous login

Management:

Camera tampering; Video motion detection (3 regions); External device through digital input; Sound
detection

Video:

Mirror, Flip, Rotation, Simultaneous triple streams, 4 Configurable regions

Performance

Number of Clients:

16

Frame Rate (fps):

30 fps at 2592 x 1944; 30 fps at 2048 x 1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 960;
30 fps at 1280 x 720; 30 fps at 800 x 600; 30 fps at 640 x 480; 30 fps at 320 x 240

Minimum illumination:

Color: 0.1 lux at F1.5 (30 IRE, 2400°K); B/W: 0.05 lux (IR LED on)

Environment

Operating Temperature (°C):

Operating Temperature: 40°C ~ 50°C (-40°F ~ 122°F)

Starting Temperature: -20°C ~ 50°C (-4°F ~ 122°F) within 30 minutes

Operating Humidity (Non-condensing):

20% ~ 80% RH

Physical Specifications

Dimensions (W x D x H mm):

139.95 x 131.17mm (5.5" x 5.2")

Weight (g):

880g (1.94lb)

Color:

White

Approval and Compliance

EMI/EMS:

CE/FCC

Safety:

IK10

Environmental Test:

IP66

Others:

ONVIF, Manufactured in ISO-9001 and ISO-14001 certified factory

Others

Supported Browsers:

Internet Explorer 8.0 or newer (full functionality)

Safari with QuickTime installed, and other browsers with VLC installed (partial functionality)

Order Information

FCS-3305

Package Contents

FCS-3305

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Screw Kit

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.