Three Phase AC Controller Modules


PSUT 230
PSUH 230

I_{RMS} = 3 x 200 A
V_{RRM} = 800-1800 V


Preliminary Data Sheet

V_{RSM} V_{DSM} (V)	V_{RRM} V_{DRM} (V)	Type	
900	800	PSUT 230/08	PSUH 230/08
1300	1200	PSUT 230/12	PSUH 230/12
1500	1400	PSUT 230/14	PSUH 230/14
1700	1600	PSUT 230/16	PSUH 230/16
1900	1800	PSUT 230/18	PSUH 230/18

W3C




W3H



Symbol	Test Conditions		Maximum Ratings	
I_{RMS}	T_C = 85 °C; 50-400 Hz (per phase)		200	A
I_{TRMS}			144	A
I_{TAVM}	T_C = 85 °C; 180° sine		90	A
I_{TSM}	T_{VJ} = 45 °C	t = 10 ms (50 Hz), sine	2250	A
	V_R = 0	t = 8.3 ms (60 Hz), sine	2400	A
	T_{VJ} = 125 °C	t = 10 ms (50 Hz), sine	2000	A
	V_R = 0	t = 8.3 ms (60 Hz), sine	2150	A
$\int i^2 dt$	T_{VJ} = 45 °C	t = 10 ms (50 Hz), sine	25300	A²s
	V_R = 0	t = 8.3 ms (60 Hz), sine	23900	A²s
	T_{VJ} = 125 °C	t = 10 ms (50 Hz), sine	20000	A²s
	V_R = 0	t = 8.3 ms (60 Hz), sine	19100	A²s
$(di/dt)_{cr}$	T_{VJ} = 125 °C	repetitive, I_T = 250 A	150	A/µs
	f=50Hz, t_P=200µs			
	V_D=2/3V_{DRM}			
	I_G=0.45 A	non repetitive, I_T = I_{TAVM}	500	A/µs
	di_G/dt=0.45A/µs			
$(dv/dt)_{cr}$	T_{VJ} = 125 °C	V_D=2/3V_{DRM}	1000	V/µs
	R_{GK} = ∞, method 1 (linear voltage rise)			
P_{GM}	T_{VJ} = 125 °C	t_P=30µs	≤ 10	W
	I_T = I_{TAVM}	t_P=300µs	≤ 5	W
P_{GAVM}			0.5	W
V_{RGM}			10	V
T_{VJ}			-40... + 125	°C
T_{VJM}			125	°C
T_{stg}			-40... + 125	°C
V_{ISOL}	50/60 Hz, RMS	t = 1 min	2500	V~
	I_{ISOL} ≤ 1 mA	t = 1 s	3000	V~
M_d	Mounting torque	(M5)	3	Nm
			26	lb. in.
Weight	typ.		86	g

Data according to IEC 60747 refer to a single thyristor unless otherwise stated



typical picture, for pin configuration see outline drawing

tentative data sheet
product still under development

Features

- Thyristor controller for AC (circuit W3C acc. to IEC) for mains frequency
- Isolation voltage 3000 V~
- Planar glass passivated chips
- Low forward voltage drop
- Leads suitable for PC board soldering
- UL Release applied

Applications

- Switching and control of three phase AC circuits
- Light and temperature control
- Softstart AC motor controller
- Solid state switches

Advantages

- Easy to mount with four screws
- Space and weight savings
- Improved temperature and power cycling capability
- High power density
- Small and light weight

POWERSEM GmbH, Walpersdorfer Str. 53
D - 91126 Schwabach
Phone: 09122 - 9764 - 0 FAX: 09122 - 9764 - 20

© 2005 POWERSEM reserves the right to change limits, test conditions and dimensions


Symbol	Test Conditions			Characteristic Value	
I_D, I_R	T_{VJ} = 125°C, V_R = V_{RRM}, V_D=V_{DRM}		≤	5	mA
V_T	I_T = 300 A,	T_{VJ} = 25 °C	≤	1.5	V
V_{TO}	For power-loss calculations only			0.85	V
r_T				2.5	mΩ
V_{GT}	V_D=6V	T_{VJ}= 25°C	≤	1.5	V
		T_{VJ}=-40°C	≤	1.6	V
I_{GT}	V_D=6V	T_{VJ}= 25°C	≤	150	mA
		T_{VJ}=-40°C	≤	200	mA
V_{GD}	T_{VJ}= 125°C	V_D=2/3V_{DRM}	≤	0.2	V
I_{GD}	T_{VJ}= 125°C	V_D=2/3V_{DRM}	≤	10	mA
I_L	T_{VJ}= 25°C, t_P=10µs		≤	450	mA
	I_G=0.45A, di_G/dt=0.45A/µs				
I_H	T_{VJ}= 25°C, V_D=6V, R_{GK}= ∞		≤	200	mA
t_{gd}	T_{VJ}= 25°C, V_D=1/2V_{DRM}		≤	2	µs
	I_G=0.45A, di_G/dt=0.45A/µs				
R_{thJC}	per thyristor; DC			0.3	K/W
	per module			0.05	K/W
R_{thJK}	per thyristor; sine 180° el			0.49	K/W
	per module			0.082	K/W
d_S	Creepage distance on surface (Pin to heatsink)			min. 11.2	mm
d_A	Strike distance in air (Pin to heatsink)			min. 11.2	mm
a	Max. allowable acceleration			50	m/s²

tentative data sheet
product still under
development


Package style and outline

Dimensions in mm (1mm = 0.0394")

W3C



W3H



POWERSEM GmbH, Walpersdorfer Str. 53
D - 91126 Schwabach
Phone: 09122 - 9764 - 0 FAX: 09122 - 9764 - 20

© 2005 POWERSEM reserves the right to change limits, test conditions and dimensions