

July, 2018

3M™ Aluminum Foil Tape 3340

Product Description

3M™ UL181A-P and UL181B-FX 3340 Aluminum Foil Tape is a high temperature, high strength aluminum foil tape coated with a cold weather acrylic pressure sensitive adhesive.

Product Features

- High strength aluminum foil backing is ideal for rigid duct board and flexible duct.
- Excellent for high heat and humidity conditions.
- Excellent performance and durability over a wide range of environmental conditions.
- Cold weather adhesive.
- Easy to install on site without special tools or application methods.



Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	Natural Aluminum		
Total Tape Thickness	0.09 mm	3.9 mil	ASTM D3652
Backing Thickness	0.05 mm	2 mil	ASTM D3652
Backing	High Strength Aluminum Foil		
Adhesive	Acrylic		
Liner	Paper		

Typical Performance Characteristics

Property	Values		Method	Backing	Notes
180° Peel Adhesion	6.6 N/cm	60 oz/in	ASTM D3330	2 mil Aluminum Foil	12 in/min (300 mm/min) 72 hr dwell on Stainless Steel
Tensile Strength	50.8 N/cm	29 lb/in	ASTM D3759		
Elongation at Break	10 %		ASTM D3759		
Temperature Use Range	-40 to 149 °C	-40 to 300 °F			

Handling/Application Information

Application Ideas

- Vapor seal on reinforced fiberglass duct board
- High performance duct closure
- Sealing flexible duct to rigid duct

Certifications

- UL181A-P Listed (UL File # MH16587)
- UL181B-FX Listed (UL File # MH16587)

Storage and Shelf Life

Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended. To obtain best performance, use this product within 24 months from date of manufacture.

Trademarks

3M and Venture Tape are trademarks of 3M Company.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all- 3m-products/~/3M-Foil-Tape-3340? N=5002385+3293241172&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/? gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=33

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Aluminum Foil Tape 3340

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



