



Configuration:

DB25M	DB25M
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
Shield	Shield

Material:

- 1.Cable: #28 25C+1+AL/MY (Beige PVC Jacket) O.D:6.5MM
- 2.Both connectors with normal type
- 3.Thumbscrew: #4-40UNC Type
- 4.Overall Molded with Beige PVC

Notes:

- 1.Total Length: *SEE "ITEM NO."
- 2.Color: Beige
- 3.Molded Type



ITEM NO	AK154-5-R (5 M)	AK162-3-R (3 M)
	AK163-7-R (7 M)	AK164-10-R (10 M)
TITLE	Serial Connection Cable fo 25-Pin Interface, D-SUB 25-Pin Male to D-SUB 25-Pin Male	

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
©Copyright 2008 by Assmann Electronic Components
All International Rights Reserved