

Data sheet | Item number: 706-5030/201-200

System cable; for Gefanuc 9030; 8 digital outputs; Length: 2 m; Conductor cross-section: 0.14 mm²

www.wago.com/706-5030/201-200



Data Notes

Note	When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.
------	---

Electrical data

Inputs/outputs	8 digital outputs
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	1 A

Connection data

Compatible PLC Modules	GE Fanuc 9030
Compatible PLC I/O Card Types	IC693 MDL730
Connection type (1)	System
Pole number 1	10
Pluggable connectors	Pluggable connector per DIN 41651; Female connector
Connection type 2	System
Pole number 2	20
Connector 2	GeFanuc IC 693 ACC 311
Cable type	LiYY
Wire cross-section	0.14 mm ²

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Color code per DIN VDE 47100

Physical data

Cable length 2 m

Material data

Weight 1.1 g

Environmental requirements

Surrounding air temperature (operation) -20 ... 50 °C

Commercial data

PU (SPU) 1 Stück

Packaging type box

GTIN 4055143044943

Downloads

Documentation

System Description

WAGO System Wiring, Selection Guide

This guide will help you select the appropriate interface modules and system cables for the controller you are using.

pdf
545.9 kB

[Download](#)

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-5030/201-200

System cable; for Gefanuc 9030; 8 digital outputs; Length: 2 m; Conductor cross-section: 0.14 mm²

[URL](#)

[Download](#)

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.