
Spezifikation für Freigabe / specification for release

Kunde / customer :
Artikelnummer / part number : **744777930**

Bezeichnung : **SPEICHERDROSSEL WE-PD**
description : **POWER-CHOKE WE-PD**

DATUM / DATE : 2008-01-04

A Mechanische Abmessungen / dimensions :



	Typ M	
A	**7,3 ± 0,3**	mm
B	**4,5 max**	mm
C	**1,5 ± 0,2**	mm
D	**1,5 ± 0,3**	mm
E	**4,0 ± 0,3**	mm


● = Start of winding Marking = Inductance code

B Elektrische Eigenschaften / electrical properties :

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Induktivität / inductance	**1 kHz / 0,25V**	L	**1000,0**	µH	**±20%**
DC-Widerstand / DC-resistance	**@ 20°C**	$R_{DC\ typ}$	**3,270**	Ω	**typ.**
DC-Widerstand / DC-resistance	**@ 20°C**	$R_{DC\ max}$	**6,000**	Ω	**max.**
Nennstrom/ rated current	**ΔT= 40 K**	I_{DC}	**0,20**	A	**max.**
Sättigungsstrom/ saturation current	**|ΔL/L|< 10%**	I_{sat}	**0,25**	A	**typ.**
Eigenres.-Frequenz / self-res.-fequency		SRF	**2,3**	MHz	**typ.**

C Lötpad / soldering spec. :

[mm]



D Prüfgeräte / test equipment :

HP 4274 A für/for L und/and Q

HP 34401 A für/for I_{DC} und/and R_{DC}

E Testbedingungen / test conditions :

Luftfeuchtigkeit / humidity:	33%
Umgebungstemperatur / temperature:	+20°C

F Werkstoffe & Zulassungen / material & approvals :

Basismaterial / base material:	Ferrit/ferrite
Endoberfläche / finishing electrode:	100% Sn
Anbindung an Elektrode / soldering wire to plating:	Sn/Ag/Cu - 96.5/3.0/0.5%
Draht / wire:	2SFBW; 155°

G Eigenschaften / general specifications :

Betriebstemp. / operating temperature: -40°C - + 125°C

Umgebungstemp. / ambient temperature: -40°C - + 85°C

It is recommended that the temperature of the part does not exceed 125°C under worst case operating conditions.

Freigabe erteilt / general release:

Kunde / customer	
.....	.....
Datum / date	Unterschrift / signature
Würth Elektronik	
.....	.....
Geprüft / checked	Kontrolliert / approved

MST	Version 10	08-01-04
MST	Version 8	04-10-11
SST	Version 7	04-07-28
SST	Version 6	04-04-21
SST	Version 5	04-04-15
MST	Version 4	03-12-10
AG	Version 3	02-11-05
AG	Version 2	02-05-14
Name	**Änderung / modification**	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Straße 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400

http://www.we-online.com

Spezifikation für Freigabe / specification for release

Kunde / customer : _____


Artikelnummer / part number : **744777930**

Bezeichnung : **SPEICHERDROSSEL WE-PD**

description : **POWER-CHOKE WE-PD**

DATUM / DATE : 2008-01-04

H Induktivitätskurve / Inductance curve :



Freigabe erteilt / general release:	Kunde / customer				
		MST	Version 10	08-01-04
		MST	Version 8	04-10-11
		SST	Version 7	04-07-28
.....	.....	SST	Version 6	04-04-21
Datum / date	Unterschrift / signature	SST	Version 5	04-04-15
	Würth Elektronik	MST	Version 4	03-12-10
		AG	Version 3	02-11-05
.....	.....	AG	Version 2	02-05-14
Geprüft / checked	Kontrolliert / approved	Name	**Änderung / modification**	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Straße 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400

http://www.we-online.com

Spezifikation für Freigabe / specification for release

Kunde / customer : _____


Artikelnummer / part number : **744777930**


Bezeichnung : **SPEICHERDROSSEL WE-PD**


description : **POWER-CHOKE WE-PD**

DATUM / DATE : 2008-01-04

I Rollenspezifikation / tape and reel specification :








Gurtspezifikation / Tape specification:		
A	**10,0 ± 0,1**	mm
B	**16,0 ± 0,2**	mm
C	**1,50** $^{+0.1}_{-0.0}$	mm
D	**4,00 ± 0,1**	mm
E	**2,00 ± 0,1**	mm
F	**1,75 ± 0,1**	mm
G	**10,0 ± 0,1**	mm
H	**5,00 ± 0,1**	mm

Rollenspezifikation / Reel specification:		
a	**330,0 ± 2,0**	mm
b	**21,00 ± 0,8**	mm
c	**13,00 ± 0,5**	mm
d	**100,0 ± 1,0**	mm



The force for tearing off cover tape is
10 to 130 grams in arrow direction

Freigabe erteilt / general release:

Kunde / customer
.....
Datum / date
.....
Unterschrift / signature

Würth Elektronik
.....
Geprüft / checked
.....
Kontrolliert / approved

MST	Version 10	08-01-04
MST	Version 8	04-10-11
SST	Version 7	04-07-28
SST	Version 6	04-04-21
SST	Version 5	04-04-15
MST	Version 4	03-12-10
AG	Version 3	02-11-05
AG	Version 2	02-05-14
Name	**Änderung / modification**	Datum / date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Straße 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400

http://www.we-online.com