



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	CD with software Relay board Smart UPS signalling RS-232 cable User manual
Performance multiplier	1
Number of tare power	50 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Server Telecom
UPS size	WS
Value multiplier	1

Physical

Cable length	2.44 M
Number of rack unit	3U
Colour	Black
Depth	66 Cm
Height	43.2 Cm
Mounting location	Front
Mounting preference	Lower
Net weight	54.55 Kg
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	No
Width	13 Cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Plug standard	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
Input voltage limits	100...280 V adjustable 180...270 V
Inputvolt_other	220 V 240 V
Number of cables	1
Input voltage	230 V

Output

Rated power in W	2100 W
Maximum configurable power in W	2100 W
Harmonic distortion	Less than 3 %
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains
Outputvolt_other	220 V 240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	8 IEC 60320 2 IEC Jumpers 2 IEC 60320
Bypass type	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve fixed loss	0.0277
Curve load maximum	100 %
Curve load minimum	3 %
Curve proportional loss	0.0402
Curve square loss	0.0238
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and-balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	3000 VA
Rated power in VA	3000 VA

Conformance

Product certifications	CE DNV KCC
Standards	EN 50091-1 EN 50091-2 EN 55022 class A EN 60950 EN 61000-3-2

Environmental

Ambient air temperature for operation	0...55 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0.00...15240.00 M
Acoustic level	55 dBA
Heat dissipation	609 Btu/H
Show note OP temperature	No
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	2
Battery recharge time	2.5 H
Number of battery replacement quantity	1
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery curve	C
Battery charger power	359 W rated
Battery power in VAH	900 VAh runtime
Battery life	3...5 Year(S)
Battery option	SURT192XLBP 1 2820 VAh SURT192XLBP 2 4740 VAh SURT192XLBP 3 6660 VAh SURT192XLBP 4 8580 VAh SURT192XLBP 5 10500 VAh SURT192XLBP 6 12420 VAh SURT192XLBP 8 16260 VAh SURT192XLBP 10 20100 VAh
Extended runtime	1

Communications & Management

Free slots	0
Preinstalled device	Dry contact I/O smartslot card
Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : overload and bypass indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous-tone alarm
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	555 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	63.64 Kg
Package 1 Height	34.7 Cm
Package 1 width	60.3 Cm
Package 1 Length	98 Cm
Number of Units in Package 3	6

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace, optional extended warranties available, optional on-site-services available
----------	--

Product Life Status : **Commercialised**