Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION

9899 Hook-up/Lead - Test Prod Wire

For more Information please call

1-800-Belden1

General Description:

Tinned copper conductor, PVC insulation. Use test probe leads for electrical and electronic measuring for test equipment.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	18	65x36	TC - Tinned Copper

Total Number of Conductors:	1

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PVC - Polyvinyl Chloride	1.2192

Overall Insulation

Overall Cable

Overall Nominal Diameter:	3.658 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL AWM Style:	1855
UL Rating:	5000 V, 80°C
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No

Electrical Characteristics (Overall)

Suggested Working Voltage:	5000 V RMS

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9899 002100	100 FT	2.100 LB	RED		#18 STR PVC TEST PROD RED
9899 0021000	1,000 FT	15.000 LB	RED		#18 STR PVC TEST PROD RED
9899 002500	500 FT	7.500 LB	RED		#18 STR PVC TEST PROD RED
9899 005500	500 FT	7.500 LB	GREEN, DARK		#18 STR PVC TEST PROD DGRN
9899 009500	500 FT	7.500 LB	WHITE		18 STR PVC TEST PROD WHT
9899 010100	100 FT	2.100 LB	BLACK		#18 STR PVC TEST PROD BLK
9899 0101000	1,000 FT	15.000 LB	BLACK	C	#18 STR PVC TEST PROD BLK
9899 010500	500 FT	7.500 LB	BLACK		#18 STR PVC TEST PROD BLK

Notes:
C = CRATE REEL PUT-UP.

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION

9899 Hook-up/Lead - Test Prod Wire

Revision Number: 1 Revision Date: 05-14-2007

© 2015 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.
Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.
All sales of Belden products are subject to Belden's standard terms and conditions of sale.
Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.
Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.