Bulletin #1407033

User Registration
Register today to create your account on Silabs.com. Your personalized profile allows you to receive technical document updates, new product announcements, "how-to" and design documents, product change notices (PCN) and other valuable content available only to registered users. http://www.silabs.com/profile

Bulletin Date: 7/3/2014	**Bulletin Effective Date:** 7/3/2014	
Title: EFM32G Datasheet Revision Notification		
Originator: Ted Batey	**Phone:** 512-532-5279	**Dept:** Marketing
Customer Contact: Kathy Haggar	**Phone:** 512-532-5261	**Dept:** Sales

Bulletin Details

Description:
Silicon Labs is pleased to announce that version 1.80 of the EFM32G (Gecko family) datasheets and version 1.10 of the EFM32G reference manual are now available. The affected datasheets are: EFM32G200, EFM32G210, EFM32G222, EFM32G230, EFM32G232, EFM32G280, EFM32G290, EFM32G840, EFM32G842, EFM32G880, EFM32G890. The affected reference manual is: EFM32G-RM.

The datasheet revision includes a number of key changes to existing Min/Max/Typ values that more accurately reflect the performance of the part. These changes are summarized in Table 1 at the end of this document. In addition, Table 3.12 HFRCO has a new Footnote 5, ensuring frequency bands above 7MHz will always have some overlap across supply voltage and temperature.

In addition, new min/max data has been added and other minor updates have been made as follows:

- Updated Current Consumption information
- Updated Power Management information
- Updated GPIO information
- Updated LFXO information
- Updated HFXO information
- Updated HFRCO information and figures
- Updated ULFRCO information
- Updated ACMP information

See Table 1 at the end of this document for additional details.

The reference manual has also been changed to reflect the updated operating voltage range and current consumption information.

Reason:
Updated specifications based on the results of additional silicon characterization. There are no physical or software changes to the devices.

The information contained in this document is PROPRIETARY to Silicon Laboratories, Inc. and shall not be reproduced or used in part or whole without Silicon Laboratories' written consent. The document is uncontrolled if printed or electronically saved.

Product Identification:

Affected Part Numbers
EFM32G200F16-QFN32
EFM32G200F32-QFN32
EFM32G200F64-QFN32
EFM32G210F128-QFN32
EFM32G222F32-QFP48
EFM32G222F64-QFP48
EFM32G222F128-QFP48
EFM32G230F32-QFN64
EFM32G230F64-QFN64
EFM32G230F128-QFN64

Affected Part Numbers
EFM32G232F32-QFP64
EFM32G232F64-QFP64
EFM32G232F128-QFP64
EFM32G280F32-QFP100
EFM32G280F64-QFP100
EFM32G280F128-QFP100
EFM32G290F32-BGA112
EFM32G290F64-BGA112
EFM32G290F128-BGA112

Affected Part Numbers
EFM32G840F32-QFN64
EFM32G840F64-QFN64
EFM32G840F128-QFN64
EFM32G842F32-QFP64
EFM32G842F64-QFP64
EFM32G842F128-QFP64
EFM32G880F32-QFP100
EFM32G880F64-QFP100
EFM32G880F128-QFP100
EFM32G890F32-BGA112
EFM32G890F64-BGA112
EFM32G890F128-BGA112

This change is considered a minor change which does not affect form, fit, function, quality, or reliability. The information is being provided as a customer courtesy.

Please contact your local Silicon Laboratories sales representative with any questions about this notification. A list of Silicon Laboratories sales representatives may be found at www.silabs.com

Customer Actions Needed:
None. Please see your Silicon Labs sales representatives if you have questions. A list of Silicon Labs sales representatives is available at www.silabs.com

Table 1: EFM32Gxxx Datasheet Rev 1.80 - Summary of Key Changes

				Datasheet Rev 1.71			Datasheet Rev 1.80			
Table*	**Symbol**	**Parameter**	**Condition**	**Min**	**Typ**	**Max**	**Min**	**Typ**	**Max**	**Unit**
3.2 General Operating Conditions	V_{DDOP}	Operating Supply Voltage		1.85		3.8	1.98		3.8	V
3.6 Power Management	$V_{BODextthr-}$	BOD threshold, falling external supply		1.82		1.85	1.74		1.96	V
3.7 Flash	V_{FLASH}	Flash erase/write supply voltage		1.8		3.8	1.98		3.8	V
3.8 GPIO	V_{IOOH}	Output high voltage	Sourcing 6 mA, V_{DD} = 1.98V	$0.75V_{DD}$			$0.75V_{DD}$			V
			Sourcing 6 mA, V_{DD} = 3.0V	$0.95V_{DD}$			$0.85V_{DD}$			V
			Sourcing 20 mA, V_{DD} = 1.98V	$0.7V_{DD}$			$0.6V_{DD}$			V
			Sourcing 20 mA, V_{DD} = 3.0V	$0.9V_{DD}$			$0.8V_{DD}$			V
	V_{IOOL}	Output low voltage	Sinking 6 mA, V_{DD} = 1.98V			$0.25V_{DD}$			$0.3V_{DD}$	V
			Sinking 6 mA, V_{DD} = 3.0V			$0.05V_{DD}$			$0.2V_{DD}$	V
			Sinking 20 mA, V_{DD} = 1.98V			$0.3V_{DD}$			$0.35V_{DD}$	V
			Sinking 20 mA, V_{DD} = 3.0V			$0.1V_{DD}$			$0.2V_{DD}$	V
	I_{IOLEAK}	Input leakage current				±25		±0.1	±100	nA
3.13 ULFRCO	f_{ULFRCO}	Oscillation frequency		0.8		1.5	0.7		1.75	kHz
3.16 ACMP	$V_{ACMPOFFSET}$	Offset voltage			10			0		mV

* Note: Table numbers may vary by datasheet. Numbers listed refer to EFM32G890.

The information contained in this document is PROPRIETARY to Silicon Laboratories, Inc. and shall not be reproduced or used in part or whole without Silicon Laboratories' written consent. The document is uncontrolled if printed or electronically saved.