

Specifications

Parameter		Unit	Minimum	Typical	Maximum
Center Frequency		MHz	69.85	70	70.15
Insertion Loss		dB	-	22.6	24
3 dB Bandwidth		MHz	11.6	11.74	-
Passband Variation		dB	-	1.1	1.5
Absolute Delay		usec	-	3.29	4
Ultimate Rejection	f0±6.3MHz	dB	35	38	-
	f0±6.5MHz	dB	40	44	-
	f0±6.9MHz	dB	50	54	-
	f0±10.9MHz	dB	52	60	-
Material Temperature coefficient		KHz/°C	-5.74		
Ambient Temperature		°C	25		
Package Size		DIP3512 (35.0x12.8x4.7mm3)			

Notes:

1. All specifications are based on the test circuit shown
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. This is the optimum impedance in order to achieve the performance show

Matching Configuration



Source / Load Impedance = 50 ohm


Notes - Component values may change depending on board layout.



SIPAT Co., Ltd.
(CETC No. 26 Research Institute)
Nanping Huayuan Road No. 14
Chongqing, China, 400060

Part Number	LBN70A36		
Rev. Date	2010-11-18		
Rev.	1.1	Page 1/3	

Package Dimension



Input	1
Output	5
Ground	2,3,4,6

Package: DIP3512

Unit: mm




SIPAT Co., Ltd.
(CETC No. 26 Research Institute)
Nanping Huayuan Road No. 14
Chongqing, China, 400060


Part Number	LBN70A36	
Rev. Date	2010-11-18	
Rev.	1.1	Page 2/3

Typical Performance


Frequency Response




Passband Response




Group Delay Variation(f0±5.5MHz)




Phase Linearity(f0±5.5MHz)



Smith Chart S11



Smith Chart S22



SIPAT Co., Ltd.
(CETC No. 26 Research Institute)
Nanping Huayuan Road No. 14
Chongqing, China, 400060

Part Number	LBN70A36	
Rev. Date	2010-11-18	
Rev.	1.1	Page 3/3