

Product data sheet

Characteristics

QDM32200TN

PowerPact Q - molded case circuit breaker - 3-pole - 25 kA - 208Y/120 V - 200 A

Product availability : Stock - Normally stocked in distribution facility



Price* : 1,784.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact Q
Trip unit technology	Thermal-magnetic

Complementary

Line Rated Current	200 A
[Ue] rated operational voltage	208Y/120 V AC
Number of poles	3
Breaking capacity	25 kA 240 V AC
Continuous current rating	80 %
Breaking capacity code	D
Mounting mode	Unit mount
Electrical connection	Lugs line Terminal nut load AWG 4...300 kcmil aluminium/copper
Magnetic hold current	1200 A
Magnetic tripping current	2400 A
Height	6.47 in (164.34 mm)
Maximum Width	4.5 in (114.30 mm)
Maximum Depth	3.93 in (99.82 mm)
Tightening torque	247.82 lbf.in (28 N.m) 0.04...0.23 in ² (25...150 mm ²) AWG 4...300 kcmil)

Environment

Product certifications	CSA IEC UL Listed
------------------------	-------------------------

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Sep 18, 2020

Ordering and shipping details

Category	00187 - Q2M REPL MAIN CB
Discount Schedule	DE2A
GTIN	00785901417309
Nbr. of units in pkg.	1
Package weight(Lbs)	4.59 lb(US) (2.08 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	6.20 in (15.748 cm)
Package 1 width	6.20 in (15.748 cm)
Package 1 Length	9.80 in (24.892 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------