

DESCRIPTION

- With TO-220 package
- Complement to type D44C Series
- Very low collector saturation voltage
- Fast switching

APPLICATIONS

- Designed for various specific and general purpose application
- Shunt and switching regulators
- Low and high frequency inverters converters and etc.

PINNING

PIN	DESCRIPTION
1	Emitter
2	Collector; connected to mounting base
3	Base

D45C Series




Fig.1 simplified outline (TO-220) and symbol

Absolute maximum ratings ($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	D45C1,2,3	-40	V
		D45C4,5,6	-55	
		D45C7,8,9	-70	
		D45C10,11,12	-90	
V_{CEO}	Collector-emitter voltage	D45C1,2,3	-30	V
		D45C4,5,6	-45	
		D45C7,8,9	-60	
		D45C10,11,12	-80	
V_{EBO}	Emitter-base voltage	Open collector	-5	V
I_C	Collector current (DC)		-4	A
I_{CM}	Collector current -peak		-6	A
I_B	Base current (DC)		-1	A
P_D	Total power dissipation	$T_C=25^\circ\text{C}$	30	W
T_j	Junction temperature		150	$^\circ\text{C}$
T_{stg}	Storage temperature		-55~150	$^\circ\text{C}$



Silicon PNP Power Transistors

D45C Series

CHARACTERISTICS


Tj=25°C unless otherwise specified

SYMBOL	PARAMETER		CONDITIONS	MIN	TYP.	MAX	UNIT
V_{CEsat}	Collector-emitter saturation voltage	D45C2,3,5,6,8,9,11,12	$I_C=-1A ; I_B=50mA$			-0.5	V
		D45C1,4,7,10	$I_C=-1A ; I_B=0.1A$				
V_{BEsat}	Base-emitter saturation voltage		$I_C=-1A ; I_B=0.1A$			-1.3	V
I_{CES}	Collector cut-off current		$V_{CE}=\text{Rated } V_{CES}$			-100	μA
I_{EBO}	Emitter cut-off current		$V_{EB}=5V ; I_C=0$			-10	μA
h_{FE-1}	DC current gain	D45C2,3,5,6,8,9,11,12	$I_C=-0.2A ; V_{CE}=1V$	40		120	
		D45C1,4,7,10		25			
h_{FE-2}	DC current gain	D45C1,4,7,10	$I_C=-1A ; V_{CE}=1V$	10			
		D45C2,5,8,11		20			
		D45C3,6,9,12	$I_C=-2A ; V_{CE}=1V$	20			
f_T	Transition frequency		$I_C=-20mA ; V_{CE}=4V ; f=1.0MHz$		40		MHz

Switching times

t_r	Rise time	$I_C=-1.0A ; V_{CC}=-20V ; I_{B1}=-I_{B2}=0.1A$			0.2	μs
t_s	Storage time				0.6	μs
t_f	Fall time				0.3	μs

PACKAGE OUTLINE

Fig.2 outline dimensions (unindicated tolerance: ± 0.10 mm)