


CUT-OUT

	X	Y
0.75~1.25	13.6-0.1	8.7±0.1
1.25~2.00	13.7-0.1	8.7±0.1
2.00~3.00	13.8-0.1	8.7±0.1



MATERIAL:

Cover: Nylon66, UL rated: 94V-2 min
 Base: Nylon66, UL rated: 94V-2 min
 Terminal: Brass, silver or tin plated
 Rating: 6A 125V AC (UL CUL)
 3A 250V AC (UL CUL VDE CE CQC)

Function: ON-OFF

Contact Resistance: 50mΩ Max

Insulation Resistance: 100MΩ Min

Dielectric Strength: 2000VAC 1 minute

Electrical life: 10,000 cycles

Mechanical life: 50,000 cycles

Operating Temperature: -20℃~80℃

Safety Approval:     



东莞市德松电子有限公司
D-SWITCH ELECTRONICS CO.,LTD

公差 TOLERANCES	.X± 0.3	.XX± 0.15	角度 ANGLE ±1°	单位 UNIT	DIMENSION UNIT	mm.
版本 VERSION	A0	比例尺 SCALE	1:1	日期 DATE	品名 TITLE	图号 DRAWING NO
核准 APPROVED BY		核对 CHECKED BY		绘图 DRAWN BY	MR5-111-C5N-BB	MR5-111-C5N-BB_0
变更说明 CHANGE DESCRIPTION		日期 DATE		ECN NO.		
版本 VER						