
TUNG-SOL

TRIODE-PENTODE

COMPACTRON

OUTLINE DRAWING
JEDEC 9-58



BASE 12 PIN BUTTON
JEDEC E12-70

MEDIUM-MU TRIODE AND BEAM PENTODE

FOR

VERTICAL-DEFLECTION OSCILLATOR

AND VERTICAL-DEFLECTION AMPLIFIER


SERVICE

IN T.V. APPLICATIONS

COATED UNIPOTENTIAL CATHODE

ANY MOUNTING POSITION

BASING DIAGRAM
JEDEC 12DZ



BOTTOM VIEW

THE 6JZ8 IS A MEDIUM - MU TRIODE AND A BEAM PENTODE IN THE 12 PIN COMPACTRON CONSTRUCTION. THE TRIODE IS DESIGNED FOR SERVICE AS A VERTICAL-DEFLECTION OSCILLATOR AND THE PENTODE AS A VERTICAL-DEFLECTION AMPLIFIER IN TELEVISION RECEIVERS.

DIRECT INTERELECTRODE CAPACITANCES

WITHOUT EXTERNAL SHIELD

PENTODE SECTION	
GRID 1 TO PLATE (g TO p)	0.34 pf
INPUT: G1 TO (H + K + G_2 + G_3)	11 pf
OUTPUT: P TO (H + K + G_2 + G_3)	7.0 pf
TRIODE SECTION	
GRID TO PLATE (G TO P)	3.6 pf
INPUT: G TO (H + K)	2.2 pf
OUTPUT: P TO (H + K)	0.7 pf

CONTINUED ON FOLLOWING PAGE

PRINTED IN U.S.A.

CONTINUED FROM PRECEDING PAGE

HEATER CHARACTERISTICS AND RATINGS

DESIGN MAXIMUM VALUE - SEE EIA STANDARD RS-239

AVERAGE CHARACTERISTICS	6.3 VOLTS	1,200	MA
LIMITS OF APPLIED VOLTAGE		6.3 ± 0.6	VOLTS
HEATER-CATHODE VOLTAGE:			
DC COMPONENT		100	VOLTS
TOTAL DC AND PEAK		200	VOLTS
HEATER NEGATIVE WITH RESPECT TO CATHODE			
TOTAL DC AND PEAK		200	VOLTS

MAXIMUM RATINGS

DESIGN MAXIMUM RATINGS - SEE EIA STANDARD RS-239

	TRIODE SECTION	PENTODE SECTION	
	VERTICAL OSCILLATOR [A] SERVICE	VERTICAL DEFLECTION [A] AMPLIFIER SERVICE	
PLATE VOLTAGE - DC	250	250	VOLTS
PEAK PULSE PLATE VOLTAGE		2,000	VOLTS
GRID 2 VOLTAGE		200	VOLTS
PEAK NEGATIVE GRID 1 VOLTAGE	400	150	VOLTS
PLATE DISSIPATION	1.0	7.0 [B]	WATTS
GRID 2 DISSIPATION		1.8	WATTS
CATHODE CURRENT - DC	20	70	MA
PEAK CATHODE CURRENT	70	245	MA
GRID 1 CIRCUIT RESISTANCE			
WITH FIXED BIAS	1.0	1.0	MEGOHMS
WITH CATHODE BIAS	2.0	2.0	MEGOHMS

A FOR OPERATION IN A 525 - LINE, 30 - FRAME TELEVISION SYSTEM AS DESCRIBED IN "STANDARDS OF GOOD ENGINEERING PRACTICE CONCERNING BROADCAST STATIONS", FEDERAL COMMUNICATIONS COMMISSION. THE DUTY CYCLE OF THE VOLTAGE PULSE MUST NOT EXCEED 15% OF ONE SCANNING CYCLE.

B IN STAGES OPERATING WITH GRID-LEAK BIAS, AN ADEQUATE CATHODE-BIAS RESISTOR OR OTHER SUITABLE MEANS IS REQUIRED TO PROTECT THE TUBE.

CONTINUED ON FOLLOWING PAGE

CONTINUED FROM PRECEDING PAGE

CHARACTERISTICS AND TYPICAL OPERATION

	TRIODE SECTION	PENTODE SECTION		
PLATE VOLTAGE	150	45	120	VOLTS
GRID 2 VOLTAGE		110	110	VOLTS
GRID 1 VOLTAGE	-5.0	0 C	-8.0	VOLTS
PLATE CURRENT	5.5	122	46	MA
GRID 2 CURRENT		16.5	3.5	MA
AMPLIFICATION FACTOR	20			
TRANSCONDUCTANCE	2,350		7,100	μMHOS
PLATE RESISTANCE - APPROX.	8.5		11.7	KOHMS
GRID 1 VOLTAGE FOR I_b = 10 μA APPROX.	-11		-25	VOLTS

C APPLIED FOR SHORT INTERVAL (2 SECONDS) SO AS NOT TO DAMAGE TUBE.

PRINTED IN U.S.A.