

Han 3A Thermopl Cover black Lever loop25

		Part number	09 20 003 5452	
		Specification	Han 3A Thermopl Cover black Lever loop25	
		HARTING eCatalogue	https://b2b.harting.com/09200035452	
Identification				
Category	Hoods/Hou	Hoods/Housings		
Series of hoods/housings	Han $A^{\mathbb{R}}$			
Type of hood/housing	Protection of	Protection cover		
Description of hood/housing	for hoods Thermoplas With fixing o			
Version				
Size	3 A	3 A		
Locking type	Single locki	Single locking lever		
Field of application	Standard H	Standard Hoods/housings for industrial applications		
Details	for mounted	d male insert		
Technical characteristics				
Limiting temperature	-40 +125	-40 +125 °C		
Degree of protection acc. to IEC 60529	IP44 IP65 / IP67	with seal screw 09 20 000 9	918	
Type rating acc. to UL 50 / UL 50E	4 4X 12			
Material properties				
Material (hood/housing)	Polycarbon	Polycarbonate (PC)		
Colour (hood/housing)	Black	Black		
Material (locking)	Polyamide	(PA)		

Colour (locking) Black Page 1 / 2 | Creation date 2021-10-01 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead
Specifications and approvals	
Approvals	DNV GL
Commercial data	
Packaging size	10
Net weight	9.42 g
Country of origin	Romania
European customs tariff number	85389099
eCl@ss	27440208 Cap for industrial connectors