

Product data sheet

Characteristics

S8650A0C0E6E1B0A

ION8650 meter 128MB, 9S/29S/36S, 277VAC
60Hz, Ethernet 3I+4O

Product availability : Non-Stock - Not normally stocked in distribution facility



Price** : 11,419.00 USD



Main

Range	PowerLogic
Product name	PowerLogic ION8650
Device short name	ION8650A
Product or component type	Energy and power quality meter

Complementary

Power quality analysis	<ul style="list-style-type: none"> harmonic distortion programmability (logic and math functions) voltage sag and swell detection waveform capture up to the 63rd harmonic IEC 61000-4-30 class A power quality measurement IEC 61000-4-15 flicker magnitude harmonic up to the 50th transient capture EN 50160 compliance report
Device application	<ul style="list-style-type: none"> Equipment monitoring and control Co-generation and IPP monitoring Energy pulsing and totalisation Load curtailment Demand and power factor control Instrument transformer correction Tariff metering
Type of measurement	<ul style="list-style-type: none"> Power factor total Power factor per phase Apparent power total Apparent power per phase Active power total Active power per phase Reactive power total Reactive power per phase Current Voltage

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	Frequency
Supply voltage	120...277 V AC 47...63 Hz
Network frequency	60 Hz
Line Rated Current	1 A 5 A 2 A
Poles description	3P 3P + N 1P + N
Power consumption in VA	24 VA
Maximum power consumption in VA	33 VA
Display type	FSTN transreflective LCD
Form designation	9S 3-element 4 36S 2½-element 4 29S 2½-element 4
Sampling rate	1024 samples/cycle
Measurement current	0.001...24 A
Input type	current 0.01...20 A 0.05 Ohm)
Measurement voltage	57...277 V AC phase to neutral 100...480 V AC phase to phase
Number of inputs	3 digital 0.001...100 mA 30 V DC
Measurement accuracy	Current 0.1 % Voltage 0.1 % Power 0.1 % Power factor 0.1 % Frequency 0.001 Hz Energy 0.1 %
Accuracy class	Class 0.2S energy IEC 62053-22 Class 0.2S energy IEC 62053-23 Class 0.2 energy ANSI C12.20
Number of outputs	2 pulse 4 form C relay output
Communication port protocol	TCP/IP 10/100 Mbit/s DNP3 300...115200 bauds ION 300...115200 bauds DLMS 300...115200 bauds Modbus 57600 bauds Ansi C12.18 <= 19200 bauds DNP3 10/100 Mbit/s ION 10/100 Mbit/s IEC 61850 ed. 2 10/100 Mbit/s Modbus RTU, master/slave 300...115200 bauds Modbus TCP, master/slave 10/100 Mbit/s EtherGate
Communication port support	RJ45 Ethernet SUB-D 9 RS485/RS232 infrared Terminal block RS485
Time synchronisation protocol	GPS: Truetime/Datum IRIG-B
Data recording	Sag and swell logs Historical logs GPS synchronisation Alarms Time stamping Data logs Transient logs Event logs Revenue logs Harmonics logs
Transmission rate	10/100 Mbit/s 300...115200 bauds <= 19200 bauds 57600 bauds
Memory capacity	128 MB
Web services	Web server

	Port addressing user designed Alarm notification by e-mail Robust security logs
Ethernet service	Enable/disable Ethernet protocols Enable/disable serial ports SNMP-Traps and SYSLOG
Tamperproof of settings	Protected by access code
Compatibility code	ION8650A

Environment

Electromagnetic compatibility	Electrostatic discharge immunity test IEC 61000-4-2 Susceptibility to electromagnetic fields IEC 61000-4-3 Electrical fast transient/burst immunity test IEC 61000-4-4 1.2/50 µs shock waves immunity test IEC 61000-4-5 Conducted and radiated emissionsB CISPR 22 Conducted RF disturbances IEC 61000-4-6 Immunity to impulse waves IEC 61000-4-12
Mounting mode	Socket-mounted
Mounting support	Enclosure door
Type of installation	Indoor installation
Overvoltage category	III
IP degree of protection	Front face IP65 Back IP51
Relative humidity	5...95 %
Pollution degree	2
Ambient air temperature for operation	-40...185 °F (-40...85 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Operating altitude	0...9842.52 ft (0...3000 m)
Standards	ANSI C12.1 IEC 62052-11
Width	7.01 in (178 mm)
Depth	9.33 in (237 mm)
Height	7.01 in (178 mm)
Net weight	15.43 lb(US) (7 kg)

Ordering and shipping details

Category	09758 - POWERLOGIC ION 8650 HARDWARE
Discount Schedule	PM1S
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Dichloromethane (Methylene chloride) and Bisphenol A (BPA) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.