

PJP10NA65 / PJF10NA65

650V N-Channel MOSFET


Voltage	650 V	Current	10 A



ITO-220AB-F



TO-220AB



Features

- $R_{DS(ON)}$, V_{GS}@10V,I_D@5A<1Ω
- High switching speed
- Improved dv/dt capability
- Low Gate Charge
- Low reverse transfer capacitance
- Lead free in compliance with EU RoHS 2011/65/EU directive.
- Green molding compound as per IEC61249 Std. (Halogen Free)

Mechanical Data

- Case : TO-220AB, ITO-220AB-F Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- TO-220AB Approx. Weight : 0.067 ounces, 1.89 grams
- ITO-220AB-F Approx. Weight : 0.068 ounces, 2 grams

Maximum Ratings and Thermal Characteristics (T_A=25°C unless otherwise noted)

PARAMETER		SYMBOL	TO-220AB	ITO-220AB-F	UNITS
Drain-Source Voltage		V_{DS}	650		V
Gate-Source Voltage		V_{GS}	±30		V
Continuous Drain Current		I_D	10		A
Pulsed Drain Current		I_{DM}	40		A
Single Pulse Avalanche Energy (Note 1)		E_{AS}	608		mJ
Power Dissipation	T_C=25°C	P_D	156	50	W
	Derate above 25°C		1.25	0.4	W/°C
Operating Junction and Storage Temperature Range		T_J,T_{STG}	-55~150		°C
Typical Thermal resistance					
- Junction to Case		$R_{\theta JC}$	0.8	2.5	°C/W
- Junction to Ambient		$R_{\theta JA}$	62.5	120	

- Limited only By Maximum Junction Temperature

PJP10NA65 / PJF10NA65

Electrical Characteristics (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V,I_D=250uA	650	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=250uA	2	2.8	4	V
Drain-Source On-State Resistance	$R_{DS(on)}$	V_{GS}=10V,I_D=5A	-	0.88	1.0	Ω
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=650V,V_{GS}=0V	-	0.03	1.0	uA
Gate-Source Leakage Current	I_{GSS}	V_{GS}=±30V,V_{DS}=0V	-	±10	±100	nA
Diode Forward Voltage	V_{SD}	I_S=10A,V_{GS}=0V	-	0.9	1.4	V
Dynamic (Note 4)						
Total Gate Charge	Q_g	V_{DS}=520V, I_D=10A, V_{GS}=10V (Note 2,3)	-	20	-	nC
Gate-Source Charge	Q_{gs}		-	8	-	
Gate-Drain Charge	Q_{gd}		-	7	-	
Input Capacitance	Ciss	V_{DS}=25V, V_{GS}=0V, f=1.0MHZ	-	1200	-	pF
Output Capacitance	Coss		-	140	-	
Reverse Transfer Capacitance	Crss		-	4	-	
Switching						
Turn-On Delay Time	$td_{(on)}$	V_{DD}=325V, I_D=10A, R_G=25Ω (Note 2,3)	-	40	-	ns
Turn-On Rise Time	t_r		-	74	-	
Turn-Off Delay Time	$td_{(off)}$		-	52	-	
Turn-Off Fall Time	t_f		-	35	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I_S	---	-	-	10	A
Maximum Pulsed Drain-Source Diode Forward Current	I_{SM}	---	-	-	40	A
Reverse Recovery Time	trr	V_{GS}=0V, I_S=10A	-	570	-	ns
Reverse Recovery Charge	Qrr	dI_F/ dt=100A/us (Note 2)	-	4.7	-	uC

NOTES :

1. L=30mH, I_{AS}=6.2A, V_{DD}=50V, R_G=25 ohm, Starting T_J=25°C
2. Pulse width≤300us, Duty cycle≤2%
3. Essentially independent of operating temperature typical characteristics.
4. Guaranteed by design, not subject to production testing

PJP10NA65 / PJF10NA65

TYPICAL CHARACTERISTIC CURVES




Fig.1 Output Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 Source-Drain Diode Forward Voltage




Fig.5 Capacitance vs. Drain-Source Voltage




Fig.6 Gate Charge

PJP10NA65 / PJF10NA65

TYPICAL CHARACTERISTIC CURVES




Fig.7 BV_{DSS} vs. Junction Temperature




Fig.8 On-Resistance vs. Junction Temperature




Fig.9 Threshold Voltage Variation with Temperature




Fig.10 Maximum Safe Operating Area




Fig.11 Maximum Safe Operating Area

PJP10NA65 / PJF10NA65

TYPICAL CHARACTERISTIC CURVES




Fig.13 PJP10NA65 Normalized Transient Thermal Impedance vs. Pulse Width





Fig.14 PJF10NA65 Normalized Transient Thermal Impedance vs. Pulse Width

PJP10NA65 / PJF10NA65

Packaging Information .


ITO-220AB-F Dimension

Unit: mm



TO-220AB Dimension

Unit: mm



PJP10NA65 / PJF10NA65

PART NO PACKING CODE VERSION

Part No Packing Code	Package Type	Packing type	Marking	Version
PJP10NA65_T0_00001	TO-220AB	50pcs / Tube	P10NA65	Halogen free
PJF10NA65_T0_00001	ITO-220AB-F	50pcs / Tube	F10NA65	Halogen free

PJP10NA65 / PJF10NA65

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.