HEYCO



Heyco®-Tite Aluminum Liquid Tight Cordgrips


Straight-Thru, NPT Hubs


The Ultimate in Liquid Tight Strain Relief Protection


- **Aluminum construction** provides excellent durability and performance for most **industrial applications**.
- For use in both indoor and outdoor applications to prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture, and coolants.
- IP 67 rated.
- Approved for NEMA 6 applications.
- Protect cable from damage and pull-out and are used in conduit hubs or knock-outs at the point where the electrical cable is to be terminated.
- Unique design with a combination tightening surface that includes both a hex area and a knurled surface.
- Anti-friction washer allows for easier compression.
- DFARS Compliant

CABLE DIA. RANGE				PART NO.	THREAD SIZE	UL	PART DIMENSIONS							
Minimum		Maximum		Machined Aluminum			A Clearance Hole Dia.		B Max. O.A. Length		C Thread Length		D Wrenching Flat Size	
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.	in.	mm.
.562	14,3	.688	17,5	**M5062**										
.688	17,5	.812	20,6	**M5063**										
.750	19,1	.875	22,2	**M5064**										
.875	22,2	1.000	25,4	**M5065**	NPT 1-1/4	UL	1.72	43,7	2.50	63,5	.69	17,5	2.25	57,2
1.000	25,4	1.125	28,6	**M5066**										
1.125	28,6	1.250	31,8	**M5067**										
1.250	31,8	1.375	34,9	**M5068**										
.562	14,3	.688	17,5	**M5069***										
.688	17,5	.812	20,6	**M5070**										
.750	19,1	.875	22,2	**M5071**										
.875	22,2	1.000	25,4	**M5072**	NPT 1-1/2	UL	1.97	50,0	2.50	63,5	.69	17,5	2.25	57,2
1.000	25,4	1.125	28,6	**M5073**										
1.125	28,6	1.250	31,8	**M5074**										
1.250	31,8	1.375	34,9	**M5075**										
1.250	31,8	1.375	34,9	**M5080**										
1.312	33,3	1.437	36,5	**M5081**										
1.438	36,5	1.562	39,7	**M5082**	NPT 2	UL	2.46	62,5	3.12	79,2	.80	20,3	2.83	71,9
1.562	39,7	1.688	42,9	**M5083**										
1.688	42,9	1.812	46,0	**M5084**										

Assembled O-ring **INCLUDED**. *Not UL Listed or CSA Certified.
Locknut not included - See page 3-42 for Metal Locknuts.







SUGGESTED CLEARANCE HOLE FOR NONTHREADED MOUNTING

Quick Specs

Material		Aluminum with Neoprene Sealing Gland and Viton® O-Ring
Certifications	UL	Listed under Underwriters' Laboratories File E51579
	CSA	Certified by Canadian Standard Association File 258093 Approved for NEMA 6 Applications
Flammability Rating		94V-2
Temperature Range		-40°F (-40°C) to 250°F (121°C)
IP Rating		IP 67

1-800-526-4182 • 732-286-1800 (NJ) • FAX: 732-244-8843 • www.heyco.com