YA45A11

by Burndy
Catalog ID: YA45A11

Prop 65 Notice

UNINSULATED ALUMINUM COMPRESSION TERMINAL, 1-HOLE DESIGNUL Listed 90° C600 Volts to 35 KV.

Product Details

General

Connector Type	Terminal
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Material	Aluminum
Physical Attribute - Number of Holes	1
Physical Attribute - Tongue Type	Standard
Plated	Y
Plating Type	Tin - Electro Plated
Temperature Rating	194
Trade Name	HYLUG™
UPC	781810178317
UPC 12 Digit	7818101783177

Dimensions

Dimension - B Length fraction	2-11/16 in
Dimension - B Length inch	2.65 in
Dimension - D inch	2.06 in
Dimension - Hole Size inch	0.82 in
Dimension - Hole Size mm	21 mm
Dimension - Inside Diameter inch	1.33 in
Dimension - L Length Overall mm	169 mm
Dimension - Length Overall inch	6.67 in
Dimension - N inch	0.99 in
Dimension - Outside Diameter inch	1.84 in
Dimension - Pad Width inch	2.59 in
Dimension - Z inch	1.07 in
Physical Attribute - Tongue Angle	Straight

Electrical Ratings

Rating - KVA	35 kV
Rating - Minimum Voltage	600

Voltage - Maximum	35000

Conductor Related

Conductor - AL Str Size	1250 kcmil;1272 kcmil;1300 kcmil;1351 kcmil;1400 kcmil;1431 kcmil;1500 kcmil
Conductor - AL Str Size Range	1250 kcmil-1500 kcmil
Conductor - Copper Str Size	1250 kcmil;1300 kcmil;1500 kcmil
Conductor - Copper Str Size Range	1250 kcmil-1500 kcmil

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	12

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)