

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** [1720430601](#)  
**Status:** **Active**  
**Overview:** [Super Sabre Connector System](#)  
**Description:** Super Sabre Right Angle Header, 6 Circuit, Short Solder Tail without Board Lock, Complies with the UL1977 finger proof standards

**Documents:**

|                                                               |                                                                |
|---------------------------------------------------------------|----------------------------------------------------------------|
| <a href="#">3D Model</a>                                      | <a href="#">Product Specification TS-171825-001-001 (PDF)</a>  |
| <a href="#">Drawing (PDF)</a>                                 | <a href="#">Packaging Specification PK-43789-001-001 (PDF)</a> |
| <a href="#">Product Specification PS-171825-001-001 (PDF)</a> | <a href="#">RoHS Certificate of Compliance (PDF)</a>           |

**Agency Certification**

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E29179  |

**General**

|                |                                              |
|----------------|----------------------------------------------|
| Product Family | PCB Headers                                  |
| Series         | <a href="#">172043</a>                       |
| Application    | Power, Signal, Wire-to-Board                 |
| Comments       | Operating Temperature Per USCAR-2; Class 3   |
| Overview       | <a href="#">Super Sabre Connector System</a> |
| Product Name   | Super Sabre                                  |
| UPC            | 887191565941                                 |

**Physical**

|                                |                                |
|--------------------------------|--------------------------------|
| Breakaway                      | No                             |
| Circuits (Loaded)              | 6                              |
| Circuits (maximum)             | 6                              |
| Color - Resin                  | Black                          |
| Durability (mating cycles max) | 25                             |
| First Mate / Last Break        | No                             |
| Flammability                   | 94V-0                          |
| Glow-Wire Capable              | Yes                            |
| Lock to Mating Part            | Yes                            |
| Material - Metal               | Copper                         |
| Material - Plating Mating      | Silver                         |
| Material - Plating Termination | Matte Tin, Nickel              |
| Material - Resin               | High Temperature Thermoplastic |
| Net Weight                     | 8.176/g                        |
| Number of Rows                 | 1                              |
| Orientation                    | Right Angle                    |
| PC Tail Length                 | 3.81mm                         |
| PCB Retention                  | None                           |
| Packaging Type                 | Tray                           |
| Pitch - Mating Interface       | 7.50mm                         |
| Plating min - Mating           | 0.025µm                        |
| Plating min - Termination      | 0.025µm                        |
| Polarized to Mating Part       | Yes                            |
| Surface Mount Compatible (SMC) | Yes                            |
| Temperature Range - Operating  | -40°C to +125°C                |
| Termination Interface: Style   | Through Hole                   |

**Electrical**

|                               |                 |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 30.0A per blade |
| Voltage - Maximum             | 600V AC (RMS)   |

**Solder Process Data**

|                                                |     |
|------------------------------------------------|-----|
| Duration at Max. Process Temperature (seconds) | 030 |
|------------------------------------------------|-----|



Series image - Reference only

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**China RoHS**

**REACH SVHC**

Not Contained Per  
-ED/01/2018 (15  
January 2018)

**Halogen-Free**

**Status**

**Low-Halogen**

**Need more information on product  
environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any  
non-product compliance questions.

|                 |               |
|-----------------|---------------|
| China ROHS      | Green Image   |
| ELV             | Not Relevant  |
| RoHS Phthalates | Not Contained |

**Search Parts in this Series**

[172043](#) Series

**Mates With**

[172672](#) Crimp Housing

|                                         |                    |          |
|-----------------------------------------|--------------------|----------|
| Lead-free                               | Process Capability | SMC&WAVE |
| Max. Cycles at Max. Process Temperature |                    | 003      |
| Process Temperature max. C              |                    | 260      |

**Material Info**

**Reference - Drawing Numbers**

|                         |                                      |
|-------------------------|--------------------------------------|
| Packaging Specification | PK-43789-001-001                     |
| Product Specification   | PS-171825-001-001, TS-171825-001-001 |
| Sales Drawing           | SD-172043-001                        |

This document was generated on 07/12/2018

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**