

RW 5/S

Order No.: 3073597



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3073597>

Bolt connection terminal block, Connection method: Bolt connection,
Load current : 76 A, Cross-section: 0.1 mm² - 16 mm², AWG 26 - 6,
Connection direction of the conductor to plug-in direction: 0 °,
Width: 16.3 mm, Color: gray

Commercial data

GTIN (EAN)	
sales group	A420
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 54 (NTK-2010)

Product notes

WEEE/RoHS-compliant since:
02/07/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Number of levels	1
Number of connections	2
Color	gray

Insulating material	PA
Inflammability class acc. to UL 94	V0

Dimensions

Width	16.3 mm
-------	---------

Technical data

Rated surge voltage	8 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-1
Nominal current I_N	76 A
Nominal voltage U_N	1000 V

Connection data

Conductor cross section solid min.	0.1 mm ²
Conductor cross section solid max.	16 mm ²
Conductor cross section stranded min.	0.1 mm ²
Conductor cross section stranded max.	16 mm ²
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	6
Connection method	Bolt connection
Screw thread	M5
Tightening torque, min	2.5 Nm
Tightening torque max	3 Nm

Certificates / Approvals

Certification

UL

Accessories

Item	Designation	Description
------	-------------	-------------

General

3075155	RW 5-F	Flange cover, Color: gray
---------	--------	---------------------------

Marking


0828295	TMT (EX9,5)R	Terminal marking with 9.5 mm strip height, continuous, without color print, for all terminals with ZB or ZBF groove, can be labeled using a thermal transfer printer, 1 roll = 50 m
0819194	UC-TM 12	UniCard materials for labeling terminal blocks with a marker groove, 40-section, can be labeled with BLUEMARK X1 and CMS-P1-PLOTTER, color: white
0819217	UC-TM 16	UniCard materials for labeling terminal blocks with a marker groove, 32-section, can be labeled with BLUEMARK X1 and CMS-P1-PLOTTER, color: white
0819233	UC-TMF 12	UniCard sheets, for labeling terminal blocks using a flat Zack marker strip groove, 40-section, can be labeled with BLUEMARK X1 and CMS-P1-PLOTTER, color: White
0819262	UC-TMF 16	UniCard sheets, for labeling terminals using a flat Zack marker strip groove, 32-section, can be labeled with BLUEMARK X1 and CMS-P1-PLOTTER, color: White

Tools

1205079	SZS 1,0X6,5 VDE	Screwdriver, bladed, VDE insulated, size: 1.0 x 6.5 x 150 mm, 2-component grip, with non-slip grip
---------	-----------------	--

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;