GSC4558

DUAL OPERATIONAL AMPLIFIER


Description


The GSC4558 is a monolithic integrated circuit designed for dual operational amplifier.

Features

- No frequency compensated required
- No latch-up
- Large common mode and differential voltage range
- Parameter tracking over temperature range
- Gain and phase match between amplifiers
- Internally frequency compensated
- Low noise input transistors


Package Dimensions






REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	5.80	6.20	M	0.10	0.25
B	4.80	5.00	H	0.35	0.49
C	3.80	4.00	L	1.35	1.75
D	0°	8°	J	0.375 REF.	
E	0.40	0.90	K	45°	
F	0.19	0.25	G	1.27 TYP.	

Pin Configurations



Block Diagram



Absolute Maximum Ratings at Ta = 25℃

Parameter	Symbol	Value	Unit
Supply Voltage	V_{CC}	±22	V
Differential Input Voltage	$V_{I(DIFF)}$	±18	V
Input Voltage	V_I	±15	V
Power Dissipation	P_D	400	mW
Operating Temperature Range	T_{OPR}	0 ~ +70	℃
Storage Temperature Range	T_{STG}	-65 ~ +150	℃

Electrical Characteristics (V_{CC}=15V Vee=-15V, T_A=25℃)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Supply Current, all Amp, no load	I_{CC}		-	2.3	4.5	mA
Input Offset Voltage	V_{IO}	R_S<10kΩ	-	2	6	mV
Input Offset Current	I_{IO}		-	5	200	nA
Input Bias Current	I_{BIAS}		-	30	500	nA
Common Mode Input Voltage	$V_{I(R)}$		±12	±13		V
Large Signal Voltage Gain	G_V	$V_{O(P-P)}$=±10V, R_L≧2kΩ	20	200	-	V/mV
Output Voltage Swing	$V_{O(P-P)}$	R_L≧10kΩ	-	±12	±14	V
Common Mode Rejection Ratio	CMRR	R_S≦10kΩ	70	90	-	dB
Supply Voltage Rejection Ratio	PSRR	R_S≦10kΩ	76	90	-	dB
Power Consumption	P_C		-	70	170	mV
Slew Rate	SR	Vi=±10V, R_L≧2kΩ, C_L≦100pF	1.2	2.2	-	V/μs
Rise Time	T_{RIS}	Vi=±20mV, R_L≧2kΩ, C_L≦100pF	-	0.3	-	μs
Overshoot	OS	Vi=±20mV, R_L≧2kΩ, C_L≦100pF	-	15	-	%
Input Resistance	R_i		0.3	2	-	MΩ
Output Resistance	R_O		-	75	-	Ω
Total Harmonic Distortion	THD	f=1kHz, A_V=20dB, R_L=2kΩ, V_O= $2V_{PP}$, C_L=100pF	-	0.008	-	%
Channel Separation	V_{O1}/V_{O2}		-	120	-	dB

Frequency Characteristics (V_{CC}=15V Vee=-15V, T_A=25℃)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Unity Gain Bandwidth	BW		2.0	2.8	-	MHz

Typical Performance Characteristics




Fig 1. Burst Noise vs. Rs




Fig 2. RMS Noise vs. Rs




Fig 3. Output Noise vs. Rs




Fig 4. Spectral Noise vs. Density




Fig 5. Open Loop Frequency Response




Fig 6. Phase Margin vs. Frequency




Fig 7. Positive Output Voltage Swing vs. Load Resistance




Fig 8. Power Bandwidth (Large Signal)

Important Notice:
- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:
- **Taiwan**: No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
  TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China**: (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
  TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165