



NOTES

1. FOR USE WITH .210 MAX. PANEL.

UNLESS OTHERWISE SPECIFIED:

1. TOLERANCES: FRACTIONS & 2 PLACE DECIMALS ± .010
 3 PLACE DECIMALS & .004
 T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED HALF THE SUM OF THEIR TOLERANCES.

A. REMOVE ALL BURRS, BREAK SHARP EDGES .008 MAX.
 B. NO FILLETS PERMITTED.
 C. SURFACE ROUGHNESS 63 MICRONS INCHES RMS MAX.
 D. ALL DIMENSIONS PRIOR TO PLATING.

ISSUE	CHANGED
0	ER 10651 O.S. 29 DEC 71
1	CN 11255A NLA 16 JUN 72
2	CN 11671A W/E 27 NOV 72
3	CN 13442 JL 30 JUL 74
4	CN 14154A JL 27 JAN 75
5	CN 15041A MJB 24 NOV 75
6	CN 17347L NIA 15 JUN 77
7	CN 28182 D CWE 4 AUG 80
8	CN 38026 E TML 07/06/00
9	CN 38078 E DCT 9/29/00

REF.	
FINISH	
SPCC	KER 10004
MATL.	
SPCC	

K-LOC BULKHEAD ADAPTER (F-F)	
DRAWN O.S.	DATE 13 OCT 71
APPR. L.J.	DATE 29 DEC 71

KINGS ELECTRONICS
 40 WAREHOUSES ROAD
 SUDBURY, N. Y. 14707

ITEM	QTY	DESCRIPTION	DRAWING NO.
7	2	INSULATOR	
6	1	CONTACT	
5	1	OUTER CONTACT	
4	1	OUTER CONTACT	
3	1	HEX NUT	4-4-B-M06
2	1	LOCKWASHER	4-10-2-M06
1	1	BODY	

S-D