

R 15-7+E-ISK-STI



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 15 007 3021 |
| Specification | R 15-7+E-ISK-STI |
| HARTING eCatalogue | https://b2b.harting.com/09150073021 |

Identification

| | |
|----------|---------|
| Category | Inserts |
| Series | R 15 |

Version

| | |
|--------------------|----------------------------|
| Termination method | Crimp termination |
| Gender | Male |
| Number of contacts | 7 |
| Details | for metal hoods / housings |

Technical characteristics

| | |
|---------------------------|-------------------|
| Rated current | 10 A |
| Rated voltage | 250 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 3 |
| Rated voltage acc. to UL | 600 V |
| Rated voltage acc. to CSA | 600 V |
| Insulation resistance | $>10^{10} \Omega$ |
| Limiting temperature | -40 ... +125 °C |
| Mating cycles | ≥ 500 |

Material properties

| | |
|-------------------|------------------------|
| Material (insert) | Polyamide (PA) |
| Colour (insert) | RAL 7032 (pebble grey) |



Pushing Performance

Material properties

| | |
|---|-----------|
| Material flammability class acc. to UL 94 | HB |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|----------|--|
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
|----------|--|

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 10 |
| Net weight | 5.6 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440223 Contact insert for circular connectors |