



Specification:
 Contact Resistance: 30m Ohm Max.
 Insulation Resistance: 100M Ohm Min.
 Voltage - Max;40V Maximum
 Current - Max:1.5A Maximum.
 Dielectric Withstanding Voltage: 500V AC for 1 Minute
 Durability (Life Test): 1500 Cycles
 Unmating Force:9.8 Newtone TO 39.2 Newtone Maximum.

NO.	NAME	MATERIAL	FINISH	REMARK	Q'TY
1	HOUSING	PBT G.F.	WHITE		1
2	PIN TERMINAL	BRASS; t:0.25	GOLD/TIN PLATED	Gold:30u" Ni:40~60u" TIN:120u" (100% pure Tin of lead free plating)	6
3	SHELL	BRASS; t:0.4	NICKEL PLATED	Ni:80~120u"	1
4	BOTTOM COVER	PBT G.F.	WHITE		1

RoHS compliant

Scale	1:1				Date	Name	Customer-No.
TOLERANCE					Drawn	04.09.2003	A.Menk
X.	±0.38				Approved	28.08.2009	Hellwig
X.X	±0.25						
X.XX	±0.13						
X°	±3°	② Update	28.08.2009	Dean	ASSMANN WSW components		
.X°	±1.0°	① Drawn	04.09.2003	A.Menk			
		Id.	Modification	Date	Name	Replace	Sheet

ASSMANN WSW-No.
A-IEE-TOP
 Drawing-No.
ASS 1497 CO rev02
 Replace Sheet

RoHS compliant