


VOLTAGE RANGE: 600V
CURRENT: 1.0 A

Features

- Miniature Size
- Low Forward Voltage drop
- Low Reverse Leakage Current
- High Surge Capability

Mechanical Data

- Case: DO-41
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band
- Weight: 0.35 grams (approx.)
- Mounting Position: Any
- Marking: Type Number



DO-41		
Dim	Min	Max
A	25.40	—
B	4.06	5.21
C	0.71	0.864
D	2.00	2.72
All Dimensions in mm		

Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbol	10EDB60	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	600	V
Average Rectified Output Current 50Hz Half Sine Wave Resistive Load	I_O	1.0 0.9	A
RMS Forward Current Surge Forward Current 50Hz Half Sine Wave, 1cycle, Non-repetitive	$I_{F(RMS)}$	1.57	A
Surge Forward Current	I_{FSM}	45	A
Operating Junction Temperature Range	T_{jw}	- 40 to + 150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 40 to + 150	$^\circ\text{C}$

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Unit
Peak Reverse Current	I_{RM}	$T_j = 25^\circ\text{C}, V_{RM} = V_{RRM}$	-	-	10	μA
Peak Forward Voltage	V_{FM}	$T_j = 25^\circ\text{C}, I_{FM} = 1.0\text{A}$	-	-	1.0	V
Thermal Resistance	$R_{th(j-a)}$	Junction to Ambient				$^\circ\text{C/W}$
		P.C. Board mounted*1	-	-	110	
		Without Fin *2	-	-	140	


*1: P.C. Board mounted (L=3mm, Print Land=5 x 5mm, Both Sides)

*2: Without Fin or P.C. Board mounted




SUNMATE


FORWARD CURRENT VS. VOLTAGE




AVERAGE FORWARD POWER DISSIPATION



AVERAGE FORWARD CURRENT VS. AMBIENT TEMPERATURE
Without Fin or P.C. Board



AVERAGE FORWARD CURRENT VS. AMBIENT TEMPERATURE
P.C. Board mounted (L=3mm, Print Land=5x5mm, Both Sides)



SURGE CURRENT RATINGS
f=50Hz, Half Sine Wave, Non-Repetitive, No Load

